


Did Apple Solve Persistence?

Demystifying macOS's Background Task Management



BIOS



Christopher Lopez
(Kandji)



Patrick Wardle
(Objective-See Foundation)

WHAT YOU WILL LEARN



Although the talk is largely focused on macOS's Background Task Management (BTM) - we'll also cover topics of reversing, malware detection, macOS internals, and more!

1



Internals
of macOS's BTM

2



Leveraging BTM
to detect malware


3



Bypassing BTM
(alerts & ES messaging)

SO WHAT IS BACKGROUND TASK MANAGEMENT (BTM) ?

governance of persistent items ("background tasks")




WHO CARES?

well, we do!


Allow in the Background

Applications add background items to perform tasks when the application isn't open, such as checking for software updates or syncing data. Turning off a background item may prevent these tasks from being completed.



softwareupdate

Item from unidentified developer.



OSX.DazzleSpy



Background Items Added

"softwareupdate" is an item that can run in the background. You can manage this in Login Items Settings.

```
# ./btm_monitor  
'ES_EVENT_TYPE_NOTIFY_BTM_LAUNCH_ITEM_ADD'  
~/Library/LaunchAgents/com.apple.softwareupdate.plist
```




Tools



Bypasses




...as defenders



...as hackers

BTM Internals



Background Items

1

`/System/Library/PrivateFrameworks/
BackgroundTaskManagement.framework/Versions/A/Resources/
backgroundtaskmanagementd`



Daemon

2

`/System/Library/PrivateFrameworks/
BackgroundTaskManagement.framework/Support/
BackgroundTaskManagementAgent.app`



Agent

BACKGROUNDTASKMANAGEMENTD

daemon for managing background items

```
% log stream ...
```

```
2023-03-20 10:52:28.948037-0400 0x9268 Default 0x1ee83 242 0
```

```
backgroundtaskmanagementd: [com.apple.backgroundtaskmanagement:main] registerLaunchItem:  
updated item: uuid=388DB692-E9E3-4A79-9737-F1F192978ECE, name=steamclean, type=legacy  
agent, disposition=[enabled, allowed, visible, not notified],  
identifier=com.valvesoftware.steamclean, url=file:///Users/l0psec/Library/LaunchAgents/  
com.valvesoftware.steamclean.plist
```

example unified log event

BACKGROUND TASK MANAGEMENT

- [BTMItem createItemRecord]

```
000000010000fc5c    ldr    x0, =__objc_class_ItemRecord_class    ;
argument "class" for method imp___auth_stubs___objc_alloc,
__objc_class_ItemRecord_class
000000010000fc60    bl     imp___auth_stubs___objc_alloc    ;
objc_alloc
000000010000fc64    mov    x19, x0
000000010000fc68    mov    x0, x20
000000010000fc6c    bl     type                                ; type
000000010000fc70    mov    x21, x0
000000010000fc74    mov    x0, x20
000000010000fc78    bl     identifier                        ; identifier

000000010000fc80    bl
imp___auth_stubs___objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
000000010000fc84    mov    x22, x0
000000010000fc88    mov    x0, x19
000000010000fc8c    mov    x2, x21
000000010000fc90    mov    x3, x22
000000010000fc94    bl     initWithType:identifier:        ;
initWithType:identifier:
000000010000fc98    mov    x19, x0
000000010000fc9c    mov    x0, x22                        ; argument
"instance" for method imp___auth_stubs___objc_release
```

```
000000010000fca0    bl     imp___auth_stubs___objc_release    ;
objc_release
000000010000fca4    mov    x0, x20
000000010000fca8    bl     uuid                                ; uuid
000000010000fcac    mov    fp, fp
000000010000fcb0    bl
imp___auth_stubs___objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
000000010000fcb4    mov    x21, x0
000000010000fcb8    mov    x0, x19
000000010000fcbc    mov    x2, x21
000000010000fcc0    bl     setUuid:                            ; setUuid:
000000010000fcc4    mov    x0, x21                        ; argument
"instance" for method imp___auth_stubs___objc_release
000000010000fcc8    bl     imp___auth_stubs___objc_release    ;
objc_release
000000010000fccc    mov    x0, x20
000000010000fcd0    bl     url                                ; url
000000010000fcd4    mov    fp, fp
000000010000fcd8    bl
imp___auth_stubs___objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
000000010000fcdc    mov    x21, x0
000000010000fce0    mov    x0, x19
000000010000fce4    mov    x2, x21
000000010000fce8    bl     setUrl:                            ; setUrl:
```

ITEM RECORDS CLASS

Properties

```
@class ItemRecord : NSObject<NSCopying, NSSecureCoding> {  
    ; @property uuid  
    ; @property identifier  
    ; @property disposition  
    ; @property enabled  
    ; @property allowed  
    ; @property generation  
    ; @property url  
    ; @property modificationDate  
    ; @property executablePath  
    ; @property executableModificationDate  
    ; @property name  
    ; @property developerName  
    ; @property isUnknownDeveloperRecord  
    ; @property teamIdentifier  
    ; @property lightweightRequirement  
    ; @property type  
    ; @property isDaemon  
    ; @property managed  
    ; @property bookmark  
    ; @property bundleIdentifier  
    ; @property associatedBundleIdentifiers  
    ; @property container  
    ; @property embeddedItems  
    ; @property dumpVerboseDescription
```

HOW DOES BACKGROUNDTASKMANAGEMENTD KNOW?

- [FSEventsObserver initWithURL:filterPath:]
- [FSEventsObserver handleEventWithID:url:eventFlags:]

```
@protocol
FSEventsObserverDelegate<NSObject>
```

```
@optional
```

```
- (void)eventObserver:(id)v1
didAddFileWithURL:(id)v2;
- (void)eventObserver:(id)v1
didRemoveFileWithURL:(id)v2;
- (void)eventObserver:(id)v1
didRenameFileWithURL:(id)v2;
- (void)eventObserver:(id)v1
didChangeFileWithURL:(id)v2;
- (void)eventObserver:(id)v1
didRemoveRootWithURL:(id)v2;
```


```
@end
```

```
int FSEventStreamCreate(int allocator, int callback, void * context, int pathsToWatch, int sinceWhen, int latency, int flags) {
    r0 = _FSEventStreamCreate_10002c048(allocator, callback, context, pathsToWatch, sinceWhen, latency, flags);
    return r0;
}
```

```
000000010001e840    mov     x0, x20
000000010001e844    bl      delegate                ; delegate
000000010001e848    mov     fp, fp
000000010001e84c    bl      imp___auth_stubs__objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
000000010001e850    mov     x23, x0
000000010001e854    mov     x2, x20
000000010001e858    mov     x3, x19
000000010001e85c    bl      eventObserver:didAddFileWithURL:    ;
eventObserver:didAddFileWithURL:
000000010001e860    mov     x0, x23                ; argument "instance" for method
imp___auth_stubs__objc_release
000000010001e864    bl      imp___auth_stubs__objc_release    ; objc_release
```

WHERE ARE ITEMS STORED?

`+ [BTMStore storeNameForDatabaseVersion:]`



Address	Assembly	Objective C Implementation
0000000100017368	pacibsp	; Objective C Implementation defined at 0x1000246dc (class method), DATA XREF=0x1000246dc
000000010001736c	sub sp, sp, #0x20	
0000000100017370	stp fp, lr, [sp, #0x10]	
0000000100017374	add fp, sp, #0x10	
0000000100017378	nop	
000000010001737c	ldr x0, =_OBJC_CLASS_\$_NSString	; _OBJC_CLASS_\$_NSString
0000000100017380	str x2, [sp, #0x10 + var_10]	
0000000100017384	adr x2, #0x10002dd38	; @"BackgroundItems-v%ld.btm"
0000000100017388	nop	
000000010001738c	bl stringWithFormat:	; stringWithFormat:
0000000100017390	ldp fp, lr, [sp, #0x10]	
0000000100017394	add sp, sp, #0x20	
0000000100017398	retab	

BTM version number changes for different OS versions

XPC COMMUNICATIONS

+[* listener:shouldAcceptNewConnection:]

-[SharedFileListService listener:shouldAcceptNewConnection:]
-[BTMSERVICE listener:shouldAcceptNewConnection:]
-[DaemonNotificationManager listener:shouldAcceptNewConnection:]

```
loc_1000047a4:  
    [interfaceWithProtocol @protocol(V2ServiceInterface)() retain];  
    setExportedInterface();  
    [r25 release];  
    setExportedObject();  
    setInterruptionHandler();  
    setInvalidationHandler();  
    resume();  
    addObject();  
    [r24 release];  
    [r23 release];  
    [r22 release];  
    r21 = 0x1;  
    goto loc_100004864;
```



```
@protocol V2ServiceInterface {  
    ; -fetchUserSettingsForUID:reply:  
    ; -saveUserSettings:uid:reply:  
    ; -launchdWillScanPath:reply:  
    ; -launchdDidScanPath:reply:  
    ; -registerLaunchItemWithAuditToken:parentURL:type:relativeURL:configuration:uid:reply:  
    ; -unregisterLaunchItemWithAuditToken:parentURL:type:relativeURL:uid:reply:  
    ; -invalidateLaunchItemWithBundleURL:type:itemURL:configuration:uid:reply:  
    ; -canLaunchItemWithAppURL:type:relativeURL:configuration:uid:reply:  
    ; -itemDispositionWithAppURL:type:relativeURL:configuration:uid:reply:  
    ; -effectiveItemDispositionWithAppURL:type:relativeURL:configuration:uid:reply:  
    ; -getItemWithIdentifier:uid:reply:  
    ; -getItemsMatching:uid:reply:  
    ; -getItemWithUUID:uid:reply:  
    ; -itemWithAppURL:type:relativeURL:configuration:uid:reply:  
    ; -addItem:uid:reply:  
    ; -updateItem:uid:reply:  
    ; -updateItems:uid:reply:  
    ; -removeItemWithIdentifier:uid:reply:  
    ; -removeItemWithUUID:uid:reply:  
    ; -mdmPayloadForIdentifier:reply:  
    ; -setMDMPayload:identifier:updateImmediately:reply:  
    ; -fetchUserIdentifiersAndUIDsWithReply:  
    ; -dumpDatabaseWithAuthorization:reply:  
    ; -eraseDatabaseWithAuthorization:reply:  
    ; -setAlwaysPostNotifications:reply:  
    ; -getAlwaysPostNotificationsWithReply:
```

Entitlement Check Example:

```
00000001000046fc    adr    x2, #0x100030e10    ;  
@ "com.apple.private.backgroundtaskmanagement.manage", CODE XREF=-[BTMSERVICE  
listener:shouldAcceptNewConnection:]+304  
0000000100004700    nop  
0000000100004704    mov     x0, x20  
0000000100004708    bl      valueForEntitlement:    ; valueForEntitlement:
```

WHAT DO THE RECORDS LOOK LIKE?

Example using dumpBTM :)

#26

UUID: 2CA629F0-B6A3-40C5-AABD-0DAF91B98BD5

Name: steamclean

Developer Name: Steam

Team Identifier: MXGJJ98X76

Type: curated legacy agent (0x90008)

Disposition: [enabled allowed visible notified] (11)

Identifier: com.valvesoftware.steamclean

URL: file:///Users/<username>/Library/LaunchAgents/com.valvesoftware.steamclean.plist

Executable Path: /Users/<username>/Library/Application Support/Steam/SteamApps/steamclean

Generation: 6

Assoc. Bundle IDs: [com.valvesoftware.steam]

Parent Identifier: Steam

curated legacy agent?

WHAT IS CURATED?

"Approved apps???"

- Type: curated developer (0x80020)
- Type: curated legacy daemon (0x90010)
- Type: managed curated developer (0xa0020)
- Type: managed curated legacy agent (0xb0008)
- Type: managed curated legacy daemon (0xb0010)

Different curated examples

sub_10000d5fc

```
000000010000d620    ldr    x0, [x20, #0x30]                ;
objc_cls_ref_NSBundle,_OBJC_CLASS_$_NSBundle
000000010000d624    adr    x2, #0x100031398                ;
@"com.apple.coreservices.BackgroundTaskManagement"
000000010000d628    nop
000000010000d62c    bl     bundleWithIdentifier:           ; bundleWithIdentifier:

000000010000d634    bl     imp___auth_stubs__objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
000000010000d638    mov    x21, x0
000000010000d63c    adr    x2, #0x1000313b8                ; @"attributions"
000000010000d640    nop
000000010000d644    adr    x3, #0x100031378                ; @"plist"
000000010000d648    nop
000000010000d64c    bl     pathForResource ofType:         ; pathForResource ofType:

000000010000d65c    adrp   x22, #0x100037000
000000010000d660    ldr    x0, [x22, #0xf60]                ;
objc_cls_ref_NSDictionary,_OBJC_CLASS_$_NSDictionary
000000010000d664    mov    x2, x19
000000010000d668    bl     dictionaryWithContentsOfFile:   ; dictionaryWithContentsOfFile:
```

attributions.plist in Resources directory

ATTRIBUTIONS . PLIST

`/System/Library/PrivateFrameworks/BackgroundTaskManagement.framework/Resources/attributions.plist`

```
"Adobe_Genuine_Software_Integrity_Service" => {  
  "AssociatedBundleIdentifiers" => [  
    0 => "com.adobe.acc.AdobeCreativeCloud"  
  ]  
  "Attribution" => "Adobe Creative Cloud"  
  "ProgramArguments" => [  
    0 => "/Library/Application Support/Adobe/AdobeGCCClient/  
AGSService"  
  ]  
  "TeamIdentifier" => "JQ525L2MZD"
```

example match



Apple does mention this plist in their docs:

<https://support.apple.com/guide/deployment/manage-login-items-background-tasks-mac-depdca572563/web>

WHAT ABOUT MANAGED ITEMS?

MDM? Profiles?

```
2023-09-30 07:56:27.109826-0400 0x548db0 Default 0x0 24882 0
BTMProfileService: [com.apple.backgroundtaskmanagement:mcx] cpInstallPayload: called for
A3DE68A0-4FC4-4F70-82E3-81A49485FDE7
```

```
2023-09-30 07:56:30.110404-0400 0x547f19 Default 0xf2377e 15243 0
backgroundtaskmanagementd: [com.apple.backgroundtaskmanagement:mcx] Rule 'Label: com.c.test'
from profile payload A3DE68A0-4FC4-4F70-82E3-81A49485FDE7 matched item 888EDEEE-1A43-4DED-
A637-5B6A62E8C3DB
```

Type: managed app (0x20002)

Type: managed curated developer (0xa0020)

Type: managed curated legacy agent (0xb0008)

Type: managed curated legacy daemon (0xb0010)

Type: managed developer (0x20020)

Type: managed legacy agent (0x30008)

Type: managed legacy daemon (0x30010)

Type: managed login item (0x20004)

PROFILE EXAMPLE

Installed via MDM

profiles show -type configuration

```
2023-09-30 07:56:27.217119-0400 0x548d71 Default 0x0
24880 0 mdmclient: (ConfigurationProfiles)
[com.apple.ManagedClient:ManagedClient] ESNotifyProfile
(Add): ID: com.kandji.profile.custom.40facf4d-521f-4dde-
bcd7-726bf1ab5f76 UUID: 40facf4d-521f-4dde-
bcd7-726bf1ab5f76 Org: com.test.btm Name: BTM_Test
Scope: system Source: 0

2023-09-30 07:56:27.217281-0400 0x548d71 Default 0x0
24880 0 mdmclient: [com.apple.ManagedClient:MDMDaemon]
[0:MDMDaemon:<0x548d71>] Installed configuration profile:
BTM_Test (com.kandji.profile.custom.40facf4d-521f-4dde-
bcd7-726bf1ab5f76:40facf4d-521f-4dde-bcd7-726bf1ab5f76) for
<Computer> (Source: MDM)

2023-09-30 07:56:27.351083-0400 0x42ec45 Default 0x0
5393 21 AssetCache: [com.apple.AssetCache:builtin]
Notification user info: {
    ProfileAction = Install;
    ProfileTypes = (
        "com.apple.servicemanagement"
    );
    ProfileUUID = "40facf4d-521f-4dde-bcd7-726bf1ab5f76";
    ProfileUserID = 501;
    ProfileUsername = l0psec;
}
```

```
_computerlevel[2] attribute: name: BTM_Test
_computerlevel[2] attribute: configurationDescription: (null)
_computerlevel[2] attribute: installationDate: 2023-09-30 11:56:27 +0000
_computerlevel[2] attribute: organization: com.test.btm
_computerlevel[2] attribute: profileIdentifier: com.kandji.profile.custom.40facf4d-521f-4dde-
bcd7-726bf1ab5f76
_computerlevel[2] attribute: profileUUID: 40facf4d-521f-4dde-bcd7-726bf1ab5f76
_computerlevel[2] attribute: profileType: Configuration
_computerlevel[2] attribute: removalDisallowed: FALSE
_computerlevel[2] attribute: version: 1
_computerlevel[2] attribute: containsComputerItems: TRUE
_computerlevel[2] attribute: installedByMDM: TRUE
_computerlevel[2] attribute: internaldata: TRUE
_computerlevel[2] payload count = 1
_computerlevel[2]      payload[1] name = Service Management - Managed
Login Items
_computerlevel[2]      payload[1] description = (null)
_computerlevel[2]      payload[1] type = com.apple.servicemanagement
_computerlevel[2]      payload[1] organization = (null)
_computerlevel[2]      payload[1] identifier =
com.apple.servicemanagement.A3DE68A0-4FC4-4F70-82E3-81A49485FDE7
_computerlevel[2]      payload[1] uuid =
A3DE68A0-4FC4-4F70-82E3-81A49485FDE7
```


profileUUID = 40facf4d-521f-4dde-bcd7-726bf1ab5f76

payload[1] uuid = A3DE68A0-4FC4-4F70-82E3-81A49485FDE7

BTMPROFILESERVICE

Rules? Matched Items?

Configuration Profile Installation
via MDM



BTMPProfileService (via XPC)

```
-[BTMPProfileService  
cpInstallPayload:profile:existingProfile:actions:error:]:
```

```
-(int)cpInstallPayload:(int)arg2 profile:(int)arg3 existingProfile:  
(int)arg4 actions:(int)arg5 error:(int)arg6 {
```



backgroundtaskmanagementd method

```
-[BTMStore checkMDMRulesForRecord:]
```



Rule 'Label: com.c.test' from profile payload
A3DE68A0-4FC4-4F70-82E3-81A49485FDE7 matched
item 888EDEEE-1A43-4DED-A637-5B6A62E8C3DB



Rules

BundleIdentifier
BundleIdentifierPrefix
Label
LabelPrefix
TeamIdentifier

BackgroundItems-v%ld.btm

Good opportunities for further
research :)

BACKGROUND TASK MANAGEMENT AGENT

agent in charge of notifications

```
2023-03-20 10:52:28.949931-0400 0x4f4e      Default      0x1ee83          564      0
BackgroundTaskManagementAgent: [com.apple.backgroundtaskmanagement:main] Posting advisory
notification request: identifier=388DB692-E9E3-4A79-9737-F1F192978ECE, body='`steamclean` is
an item that can run in the b...'

2023-03-20 10:52:28.949960-0400 0x4f4e      Default      0x1ee83          564      2
BackgroundTaskManagementAgent: (UserNotifications) [com.apple.UserNotifications:Connections]
[com.apple.BTMNotificationAgent] Adding notification request 928B-45D8 to destinations:
Default

2023-03-20 10:52:28.950641-0400 0x4f4e      Default      0x1ee83          564      2
BackgroundTaskManagementAgent: (UserNotifications) [com.apple.UserNotifications:Connections]
[com.apple.BTMNotificationAgent] Added notification request: [ hasError: 0
hasCompletionHandler: 1 ]
```

HOW DO NOTIFICATIONS WORK?

UserNotificiation Bundles

-[NotificationManager postManagedItemNotificationForItem:container:]

```
0000000100015180      mov      x0, x21                      ; CODE XREF=-
[NotificationManager postManagedItemNotificationForItem:container:]+160
0000000100015184      mov      w2, #0x1
0000000100015188      bl       setHaveManagedItemNotification:      ;
setHaveManagedItemNotification:

0000000100015190      ldr       x0,
=_OBJC_CLASS_$_UNMutableNotificationContent ;
_OBJC_CLASS_$_UNMutableNotificationContent
0000000100015194      bl       imp___auth_stubs___objc_opt_new          ;
objc_opt_new
0000000100015198      mov      x22, x0
000000010001519c      adr       x0, #0x100025618                      ;
@"NOTIFICATION_TITLE_MANAGED_ITEM"
00000001000151a0      nop
00000001000151a4      bl       sub_100013b50                      ;
sub_100013b50
```

sub_100013b50

```
0000000100013b6c      ldr       x19, =_OBJC_CLASS_$_NSBundle
; _OBJC_CLASS_$_NSBundle
0000000100013b70      bl       imp___auth_stubs___objc_retain          ;
objc_retain
0000000100013b74      mov      x20, x0
0000000100013b78      adr       x2, #0x1000256d8                      ; @"/
System/Library/UserNotifications/Bundles/
com.apple.BTMNotificationAgent.bundle"
0000000100013b7c      nop
0000000100013b80      mov      x0, x19
0000000100013b84      bl       bundleWithPath:                          ;
bundleWithPath:

0000000100013b8c      bl
imp___auth_stubs___objc_retainAutoreleasedReturnValue ;
objc_retainAutoreleasedReturnValue
0000000100013b90      mov      x21, x0
0000000100013b94      adr       x3, #0x1000256f8                      ; @""
0000000100013b98      nop
0000000100013b9c      mov      x2, x20
0000000100013ba0      mov      x4, #0x0
0000000100013ba4      bl       localizedStringForKey:value:table:      ;
localizedStringForKey:value:table:
```

USER NOTIFICATION BUNDLES?

BackgroundTaskManagementAgent Entitlements

Entitlements -


```
[Key] com.apple.private.CoreAuthentication.SPI
[Value]
    [Bool] true
[Key] com.apple.private.LocalAuthentication.CallerName
[Value]
    [Bool] true
[Key] com.apple.private.backgroundtaskmanagement.manage
[Value]
    [Bool] true
[Key] com.apple.private.backgroundtaskmanagement.responses
[Value]
    [Bool] true
[Key] com.apple.private.tcc.allow
[Value]
    [Array]
        [String] kTCCServiceSystemPolicyAllFiles
[Key] com.apple.private.coreservices.canaccessanysharedfilelist
[Value]
    [String] read-write
[Key] com.apple.private.sharedfilelist.AllowRestrictedItemPropertyUpdates
[Value]
    [Bool] true
[Key] com.apple.private.usernotifications.bundle-identifiers
[Value]
    [Array]
        [String] com.apple.BTMNotificationAgent
```

/System/Library/UserNotifications/Bundles/
com.apple.BTMNotificationAgent.bundle/Contents/Resources/Localizable.loctable

```
"en" => {
    "APPROVAL_AUTH_REASON" => "You must authenticate as an administrator to allow background items for all users."
    "APPROVE" => "Allow"
    "DONT_APPROVE" => "Don't Allow"
    "NOTIFICATION_BODY_APP_LOGIN_ITEM_ADVISORY" => "'%@' will open automatically when you log in. You can manage this in Login Items Settings."
    "NOTIFICATION_BODY_APPROVAL" => "'%@' added items that can run in the background for all users. Do you want to allow this?"
    "NOTIFICATION_BODY_BACKGROUND_ITEM_ADVISORY" => "'%@' added items that can run in the background. You can manage this in Login Items Settings."
    "NOTIFICATION_BODY_BACKGROUND_ITEM_ADVISORY_DEVELOPER" => "Software from '%@' added items that can run in the background. You can manage this in Login Items Settings."
    "NOTIFICATION_BODY_BACKGROUND_ITEM_ADVISORY_UNKNOWN" => "'%@' is an item that can run in the background. You can manage this in Login Items Settings."
    "NOTIFICATION_BODY_MANAGED_ITEM" => "Your organization added items that can run in the background. You can view these in Login Items Settings."
    "NOTIFICATION_TITLE_APP_LOGIN_ITEM_ADVISORY" => "Login Item Added"
    "NOTIFICATION_TITLE_APPROVAL" => "Background Items Added"
    "NOTIFICATION_TITLE_BACKGROUND_ITEM_ADVISORY" => "Background Items Added"
    "NOTIFICATION_TITLE_MANAGED_ITEM" => "Managed Login Items Added"
    "SNOOZE_ONE_DAY" => "Snooze for 1 day"
    "SNOOZE_ONE_WEEK" => "Snooze for 1 week"
```


Tools (Part I)

(reactively) detecting persistent malware via BTM



MAC MALWARE

...the vast majority persists!




The Mac Malware of 2022 🐙

A comprehensive analysis of the year's new malware

by: Patrick Wardle / January 1, 2023

2022: ~80% persisted
(all as launch items)

2021: ~90% persisted
(all as launch items)



BlockBlock
...block block'ing since 2015!


OSX.DAZZLESPY

...persistently deployed via Safari 0days

```
% strings - DazzleSpy/softwareupdate
...
%@/Library/LaunchAgents
/com.apple.softwareupdate.plist

launchctl unload %@
RunAtLoad
```

Embedded strings



/Library/LaunchAgents

```
# FileMonitor.app/Contents/MacOS/FileMonitor -pretty
...
{
  "event" : "ES_EVENT_TYPE_NOTIFY_CREATE",
  "file" : {
    "destination" : "~/Library/LaunchAgents/
                  com.apple.softwareupdate.plist",

    "process" : {
      "pid" : 1469
      "name": softwareupdate
      "path" : "/Users/user/Desktop/softwareupdate",
    }
  }
}
```

Launch agent persistence

(~/Library/LaunchAgents/com.apple.softwareupdate.plist)

and malware!

Usage: sfltool csinfo|dumpbtm|archive|clear|resetbtm|resetlist|list|list-info [options]

```

    UUID: EAE1D8DC-2928-47C1-BC53-6274590FE3D1
    Name: us.zoom.ZoomDaemon
    Developer Name: Zoom Video Communications, Inc.
    Team Identifier: BJ4HAAB9B3
    Type: legacy daemon (0x10010)
    Disposition: [enabled, allowed, visible, notified] (11)
    Identifier: us.zoom.ZoomDaemon
    URL: file:///Library/LaunchDaemons/us.zoom.ZoomDaemon.plist
    Executable Path: /Library/PrivilegedHelperTools/us.zoom.ZoomDaemon
    Generation: 1
    Parent Identifier: Zoom Video Communications, Inc.

```

sfltool (option: dumpbtm)

THE (RAW) BTM DATABASE

...a binary plist, containing serialized objects

```
% file /var/db/com.apple.backgroundtaskmanagement/BackgroundItems-v8.btm
```

Apple binary property list

```
% plutil -p /var/db/com.apple.backgroundtaskmanagement/BackgroundItems-v8.btm
```

```
{
  "$archiver" => "NSKeyedArchiver"
  "$objects" => [
    0 => "$null"
    1 => {
      "$class" => <CFKeyedArchiverUID 0x600003e57640 [0x1e69087f8]>{value = 142}
      "itemsByUserIdentifier" => <CFKeyedArchiverUID 0x600003e57660 [0x1e69087f8]>{value = 2}
      "mdmPayloadsByIdentfier" => <CFKeyedArchiverUID 0x600003e57680 [0x1e69087f8]>{value = 140}
      "userSettingsByUserIdentfier" => <CFKeyedArchiverUID 0x600003e576a0 [0x1e69087f8]>{value = 134}
      ...
    }
  ]
}
```

BTM database (contains NSKeyedArchiver)



Serialization, saves objects to a
persistent archive (e.g. BTM database)




SFLT00L'S ITEM DE-SERIALIZATION

...implemented in an "initWithCoder:" method

```
01  /* @class ItemRecord */
02  -(void *)initWithCoder:(NSCoder *)decoder {
03
04      rax = objc_opt_class(@class(NSUUID));
05      rax = [r14 decodeObjectOfClass:rax forKey:@"uuid"];
06
07      rax = objc_opt_class(@class(NSString));
08      rax = [r14 decodeObjectOfClass:rax forKey:@"executablePath"];
09
10      rax = objc_opt_class(@class(NSString));
11      rax = [r14 decodeObjectOfClass:rax forKey:@"teamIdentifier"];
12
13      ...
```

method automatically invoked
to de-serialize stored objects

BTM Daemon
[ItemRecord initWithCoder];



Q~ ItemRecord

> Tag Scope

Idx	Name
173	-[ItemRecord uuid]
174	-[ItemRecord setUuid:]
175	-[ItemRecord identifier]
176	-[ItemRecord setIdentifier:]
177	-[ItemRecord disposition]
178	-[ItemRecord setDisposition:]
179	-[ItemRecord generation]
180	-[ItemRecord setGeneration:]
181	-[ItemRecord url]
182	-[ItemRecord setUrl:]
183	-[ItemRecord modificationDate]
184	-[ItemRecord setModificationDate:]
185	-[ItemRecord executablePath]
186	-[ItemRecord setExecutablePath:]
187	-[ItemRecord executableModificationDate]
188	-[ItemRecord setExecutableModificationDate:]
189	-[ItemRecord teamIdentifier]
190	-[ItemRecord setTeamIdentifier:]

'ItemRecord' properties

PARSING THE BTM DATABASE

...(re)implemented in our own code

```
01 //load
02 // path set to BTM database
03 NSData* data = [NSData dataWithContentsOfURL:path options:0 error:NULL];
04
05 //init keyed unarchiver with database data
06 NSKeyedUnarchiver* keyedUnarchiver = [[NSKeyedUnarchiver alloc] initWithReadingFromData:data error:NULL];
07
08 //de-serialize
09 // will trigger call to "initWithCoder:" and de-serialize all objects
10 Storage* storage = [keyedUnarchiver decodeObjectOfClass:[Storage class] forKey:@"store"];
11
12 //print out all items
13 for(NSString* key in storage.items) {
14
15     NSArray* items = storage.items[key];
16
17     for(ItemRecord* item in items){
18         printf(" #d\n", ++itemNumber);
19         printf(" %s\n", [[item dumpVerboseDescription] UTF8String]);
20     }
21 }
22 }
```


my "Dump BTM" library

PARSING THE BTM DATABASE

...(re)implemented in our own code

```
01 #include "dumpBTM.h"
02
03 int main(int argc, const char * argv[]) {
04
05     //set if you want
06     // a custom btm file
07     NSURL* btmPath = nil;
08
09     //dump stdout
10     // (aka sfltool dumpbtm)
11     dumpBTM(btmPath);
12
13     //or parse into a dictionary...
14     NSDictionary* contents = parseBTM(path);
15     ...
}
```

just link in
the 'Dump BTM' library



github.com/objective-see/DumpBTM

"DUMP BTM" OUTPUT

...and no root access required

```
% ./dumpBTM
Opened /private/var/db/com.apple.backgroundtaskmanagement/BackgroundItems-v8.btm

=====
Records for UID 0 : FFFFFFFF-DDDD-CCCC-BBBB-AAAA00000000
=====

...
UUID:          EAE1D8DC-2928-47C1-BC53-6274590FE3D1
Name:          us.zoom.ZoomDaemon
Developer Name: Zoom Video Communications, Inc.
Team Identifier: BJ4HAAB9B3
Type:          legacy daemon (0x10010)
Disposition:   [enabled allowed visible notified] (11)
Identifier:    us.zoom.ZoomDaemon
URL:           file:///Library/LaunchDaemons/us.zoom.ZoomDaemon.plist
Executable Path: /Library/PrivilegedHelperTools/us.zoom.ZoomDaemon
Generation:    2
Assoc. Bundle IDs: [us.zoom.xos]
Parent Identifier: Zoom Video Communications, Inc.
```

"Dump BTM" output

KNOCKKNOCK v2.5

...now with BTM item enumeration

KnockKnock

Start Scan

Categories:

Authorization Plugins0

Browser Extensions3

Background Managed Tasks8

Cron Jobs0

Dir. Services Plugins0

Event Rules0

Extensions and Widgets3

Kernel Extensions0

Items:

CCXProcess

/Applications/Utilities/Adobe Creative Cloud Experience/CCXProcess/CCXProcess.app/Contents/MacOS/CC...

/Library/LaunchAgents/com.adobe.ccxprocess.plist

0/75

virustotal

info

show

ChmodBPF

/Library/Application Support/Wireshark/ChmodBPF/ChmodBPF

/Library/LaunchDaemons/org.wireshark.ChmodBPF.plist

0/75

virustotal

info

show

Creative Cloud

/Applications/Utilities/Adobe Creative Cloud/ACC/Creative Cloud.app/Contents/MacOS/Creative Cloud

/Library/LaunchAgents/com.adobe.AdobeCreativeCloud.plist

?

virustotal

info

show

com.adobe.acc.installer.v2

/Library/PrivilegedHelperTools/com.adobe.acc.installer.v2

/Library/LaunchDaemons/com.adobe.acc.installer.v2.plist

?

virustotal

info

show

magnetLauncher

/Applications/Magnet.app/Contents/Library/LoginItems/magnetLauncher.app/Contents/MacOS/magnetLaunchi...

0/74

virustotal

info

show

? softwareupdate

/Users/Patrick/.local/softwareupdate

/Users/patrick/Library/LaunchAgents/com.apple.softwareupdate.plist

33/75

virustotal

info

show

us.zoom.ZoomDaemon

/Library/PrivilegedHelperTools/us.zoom.ZoomDaemon

/Library/LaunchDaemons/us.zoom.ZoomDaemon.plist

0/74

virustotal

info

show

zoom.us

/Applications/zoom.us.app/Contents/MacOS/zoom.us

?

virustotal

info

show

KnockKnock


version: 2.4.0

OSX.DazzleSpy

Scan Complete

Tools (Part II)

(proactively) detecting persistent malware via BTM



BTM DAEMON'S REFERENCES TO "ENDPOINT SECURITY"

```
% strings - backgroundtaskmanagementd | grep ES

submitItemAddToES: No URL provided, cannot submit event to EndpointSecurity
submitItemAddToES: Invalid BTMItemType, cannot submit event to EndpointSecurity
```

References to 0x100007b84

Address	Value
0x10000383b (-[SFLClientProcess addURL:managed:reply:] + 0x677)	call submitItemAddToES
0x1000038ac (-[SFLClientProcess addURL:managed:reply:] + 0x6e8)	call submitItemAddToES
0x100005053 (-[BTMService registerLaunchItemWithAuditToken:parentURL:type:relativeUR...	call submitItemAddToES
0x100005084 (-[BTMService registerLaunchItemWithAuditToken:parentURL:type:relativeUR...	call submitItemAddToES
0x10000519c (-[BTMService registerLaunchItemWithAuditToken:parentURL:type:relativeUR...	call submitItemAddToES
0x1000051cc (-[BTMService registerLaunchItemWithAuditToken:parentURL:type:relativeUR...	call submitItemAddToES
0x1000065dd (-[BTMService addItem:uid:reply:] + 0x1ef)	call submitItemAddToES
0x100006611 (-[BTMService addItem:uid:reply:] + 0x223)	call submitItemAddToES

Cancel

01

02

03

04

submitItemAddToES:

...

b1

ess_notify_btm_launch_item_add

Google


"ess_notify_btm_launch_item_add"

Your search - "ess_notify_btm_launch_item_add" - did not match any documents.

very undocumented :/

implemented in:

libEndpointSecuritySystem.dylib




ENDPOINT SECURITY

ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_ADD event

```
01  /* The valid event types recognized by EndpointSecurity */
02  typedef enum {
03      ...
04
05  // The following events are available beginning in macOS 13.0
06  ...
07      ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_ADD,
08      ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_REMOVE
```

❶ Something persists



/Library/LaunchDaemons

❷



picked up by BTM subsystem



❸

deliver notification






ES "client"

ENDPOINT SECURITY


ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_ADD event

❶ Something persists




/Library/LaunchDaemons

❷ Picked up by BTM



❸ Delivers notification



ES "client"

```
01  /* The valid event types recognized by EndpointSecurity */
02  typedef enum {
03      ...
04
05  // The following events are available beginning in macOS 13.0
06  ...
07      ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_ADD,
08      ES_EVENT_TYPE_NOTIFY_BTMLAUNCH_ITEM_REMOVE
```

HOORAY, PERSISTENT MALWARE DETECTION!

...via `ES_EVENT_TYPE_NOTIFY_BTM_LAUNCH_ITEM_ADD`

system alert



Background Items Added

"softwareupdate" is an item that can run in the background. You can manage this in Login Items Settings.

```
# ./btm_monitor
New Event: 'ES_EVENT_TYPE_NOTIFY_BTM_LAUNCH_ITEM_ADD'

Type: ES_BTM_ITEM_TYPE_AGENT


Instigator: /usr/libexec/smd

Agent exe: /Users/User/.local/softwareupdate
Agent url: /Users/User/Library/LaunchAgents/com.apple.softwareupdate.plist
```

(our) persistence detection
(OSX.DazzleSpy)


Breaking

...avoiding BTM alerts & ES messages



HACKERS HATE ALERTS (& MESSAGES)

...that can give away their attack



BYPASS SYSTEM ALERT (METHOD 0x1)

reset the BTM database, via sfltool

note: requires root privileges

```
# sfltool resetbtm  
sfltool[1261:13567] Database reset.
```




```
% log stream --debug --info --predicate "process = 'backgroundtaskmanagementd'"  
backgroundtaskmanagementd: registerLaunchItem: result=no error, new item  
disposition=[enabled, allowed, visible, not notified],  
identifier=com.apple.softwareupdate,  
url=file:///Users/user/Library/LaunchAgents/com.apple.softwareupdate.plist  
  
backgroundtaskmanagementd: should post advisory=false for uid=501,  
id=6ED3BEBEBC-8D60-45ED-8BCC-E0163A8AA806, item=softwareupdate
```

"should post advisory=false"

BYPASS SYSTEM ALERT (METHOD 0x2)

pause, then kill the BTM agent



```
% pgrep BackgroundTaskManagementAgent  
88262
```

```
% kill -SIGSTOP 88262
```

```
% ps -o state 88262  
T
```


```
% kill -SIGKILL 88262
```

'T' means, stopped

- 1 Get pid of BTM agent
- 2 Send it a 'STOP' signal
- 3 Once persisted, kill it (to prevent alert re-delivery)

BYPASS ES EVENTS

prevent `ES_EVENT_TYPE_NOTIFY_BTM_LAUNCH_ITEM_ADD`



```
# ./btm_monitor
New Event: 'ES_EVENT_TYPE_NOTIFY_BTM_LAUNCH_ITEM_ADD'


item exe: /Users/User/.local/softwareupdate
item url: /Users/User/Library/LaunchAgents/com.apple.softwareupdate.plist
```

want to prevent this!

```
01 def submitItemAddToES()
02     ...
03     ess_notify_btm_launch_item_add();
```

found in
`libEndpointSecuritySystem`

```
01 def ess_notify_btm_launch_item_add()
02     ...
03     downcallNotifyOnly();
```



```
01 def downcallNotifyOnly()
02     ...
03     if(!mac_syscall("EndpointSecurity", ...))
04         os_log_impl(..., "Failed to submit event using ES syscall %d: %d %s", &var_50, 0x18);
```

mac_syscall: to the kernel

(RESPONSIBLE?) PROCESS LOOKUP

...via `proc_find` & `proc_getexecutablenode`

```
% lladb  
(lldb) gdb-remote 8084
```

```
...  
(lldb) bt  
EndpointSecurity`pdbReadAuditToken()
```

```
...  
EndpointSecurity`EndpointSecurityEventManager::sendNotifyOnly()  
EndpointSecurity`EndpointSecurityEventManager::sendBtmLaunchItemAdd()  
EndpointSecurity`EndpointSecurityEventManager::es_policy_syscall()  
kernel`hndl_unix_scall64
```

call stack

EndpointSecurity.kext

```
01 def pdbReadAuditToken()  
02 ...  
03 PackedDataBufferReader::read  
04 ...  
05 AutoReleasingProc::createFromPidVer();  
06 ...  
07 set_common_proc_info();  
08  
09 //error? no ES message delivered!
```

```
01 def AutoReleasingProc::createFromPidVer();  
02 ...  
03 proc* process = proc_find(<pid>);
```

```
(lldb) p *(proc*)$rdi  
(proc) $1 = {  
  p_pid = 866  
  p_name = {'OverSight'}
```


reported event
(in user-mode)

```
01 def set_common_proc_info();  
02 ...  
03 vnode = proc_getexecutablenode(process);  
04 if(!vnode)  
05     //set error to 0x3 (ESRCH / "No Such Process")
```

```
# eslogger btm_launch_item_add  
"event": {  
  "btm_launch_item_add": {  
    "pid": 866  
    "path": "/Applications/OverSight.app  
             /Contents/MacOS/OverSight"  
    ...
```

(RESPONSIBLE?) PROCESS LOOKUP

...via `proc_find` & `proc_getexecutablenode`



What happens if the responsible process ...has (quickly) exited already?

```
01 def AutoReleasingProc::createFromPidVer();
02 ...
03 proc* process = proc_find(NULL)
```

`proc_find(NULL/0)`
...will return the kernel task

```
(lldb) p *(proc*)$rdi
(proc) $1 = {
  p_pid = 0
  p_name = {'kernel_task'}
```

```
01 def set_common_proc_info();
02 ...
03 vnode = proc_getexecutablenode(process)
04 if(!vnode)
05     //return ERROR 0x3: ('ESRCH' / "No Such Process")
06     rax = 0x3;
```

the kernel task: no executable vnode!

Error
...and no ES message delivered! 🤔

```
% log stream ...
```

```
Error
backgroundtaskmanagementd: (libEndpointSecuritySystem.dylib)
Failed to submit event using ES syscall 20: 3 No such process
```

HOW TO TRIGGER?


...as easy as installing BlockBlock 😊💧

```
01 #install logic
02 if [ "${1}" == "-install" ]; then
03     ...
04
05     cp "com.objective-see.blockblock.plist" /Library/LaunchDaemons/
06
07     echo "launch daemon installed"
```

BlockBlock Installer

Conclusions

...& take aways



TAKEAWAYS

